

# GM Lighting

## LEDTASK™ STANDARD OUTPUT FLEXIBLE LED LINEAR RIBBON

Project: \_\_\_\_\_

Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact Phone: \_\_\_\_\_

### PRODUCT DESCRIPTION

LEDTask is a flexible LED linear ribbon that conforms to straight, curved and irregular architectural covers, bannisters, recesses, and other constructs where even, energy saving LED illumination is specified. Available in a 5 meter (16.4') reel, LEDTask can be cut in the field to achieve virtually any custom installation.

Available in 5500K\* Pure White, 2700K\* and 3500K\* Warm White, Red, Blue, Green and Amber.

### PRODUCT SPECIFICATIONS

**Construction:** LEDTask is a flexible LED ribbon that conducts power via the LTW series ribbon to power supply connectors. Included in each reel are 3 LTW-24 connectors and 1 LTW-24 affixed to start of reel.

**Electrical:** Each of the 300 LED's per reel (19 LED's per foot) are .08W, equalling 1.52 watts per foot. Total Amps per reel is 2. 50,000 hr. life.

**Temperature:** 2700K, 3500K and 5500K.

**Power Supplies:** See chart at right for complete descriptions and catalog numbers.

**Dimming:** Available with GM Lighting dimming power supplies (see right).

**Mounting:** 3M double stick mounting tape pre-affixed to LEDTask Flexible Ribbon.

### Connectors:

See chart below

**Label:** UL listed. American Lighting Association

\* Kelvin temperature (color) ±200




### FLEXIBLE LED RIBBON CONNECTORS

Cat. No.	Description
LTC-1	Ribbon to Ribbon Connector
LTC-3	3" Flexible Ribbon to Ribbon Connector
LTC-12	12" Flexible Ribbon to Ribbon Connector
LTC-24	24" Flexible Ribbon to Ribbon Connector
LTC-36	36" Flexible Ribbon to Ribbon Connector
LTC-60	60" Flexible Ribbon to Ribbon Connector
LTW-6	6" Flexible Ribbon to Power Supply Connector
LTW-24	24" Flexible Ribbon to Power Supply Connector
LTW-48	48" Flexible Ribbon to Power Supply Connector

### ORDERING DETAIL

Cat. Number	Length	Total LED's	LED Wattage	Total Amps	Lumens per Ft.*	Color	LED Life
LTR300-SO-27	5M / 16.4'	300 (19/ft.)	.08W (1.52W/ft.)	2.0	65	2700K Warm White	50,000 hrs.
LTR300-SO-WW	5M / 16.4'	300 (19/ft.)	.08W (1.52W/ft.)	2.0	79	3500K Warm White	50,000 hrs.
LTR300-SO-PW	5M / 16.4'	300 (19/ft.)	.08W (1.52W/ft.)	2.0	131	5500K Pure White	50,000 hrs.
LTR300-RD	5M / 16.4'	300 (19/ft.)	.08W (1.52W/ft.)	2.0	9	Red	50,000 hrs.
LTR300-BL	5M / 16.4'	300 (19/ft.)	.08W (1.52W/ft.)	2.0	12	Blue	50,000 hrs.
LTR300-GR	5M / 16.4'	300 (19/ft.)	.08W (1.52W/ft.)	2.0	34	Green	50,000 hrs.
LTR300-AM	5M / 16.4'	300 (19/ft.)	.08W (1.52W/ft.)	2.0	10	Amber	50,000 hrs.

\*Kelvin temperature (color) ±200. Updated lumen output data (10-01-09)



### ELECTRONIC POWER SUPPLIES DIMMABLE MAGNETIC POWER SUPPLIES

Cat. No.	Description
LTP-2	2 Amp - Switchable - 120V Cord and Plug. 12VDC @ 2 amps. Electronic.
LTP-6	6 Amp - Switchable - 120V Cord and Plug. 12VDC @ 6 amps. Electronic.
LTH-2	2.1 Amp - 12V DC - 25W Metal Chassis Hardwire Screw terminals
LTH-4	4.2 Amp - 12V DC - 50W Metal Chassis Hardwire Screw terminals
LTH-8	8.5 Amp - 100W Metal Chassis Hardwire Screw terminals and mounting feet. Electronic.
LTH-16	16.7 Amp - 200W Metal Chassis Hardwire Screw terminals and mounting feet. Electronic.
LTH-25	25 Amp - 320W Metal Chassis Hardwire Screw terminals and mounting feet. Electronic.
LTH-50-DIM	Dimmable - Primary: 120VAC, 60Hz, 0.33A Secondary: 12VAC, 12VDC, 3.33A Max. 50W
LTH-60-DIM	Dimmable - Primary: 120VAC, 60Hz, 0.33A Secondary: 12VAC, 12VDC, 3.33A Max. 60W
LTHM-100-DIM	Dimmable - Input: 120VAC, 60Hz, Output: 12VDC Max. 100W, Nema 3R Enclosure

For power supply dimensions, please see [www.gmlighting.net](http://www.gmlighting.net)



GM Lighting, LLC • 9830 W. 190th St. • Unit F • Mokena, IL 60448  
Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • [www.gmlighting.net](http://www.gmlighting.net)  
e-mail: [gmlightingllc@sbcglobal.net](mailto:gmlightingllc@sbcglobal.net) • Specifications subject to change without notice.

ledtaskso\_030810