

# 120VAC IC RATED MINI-DIMMABLE AND ADJUSTABLE LED DOWNLIGHT

**GM Lighting**®

Project Name	Type
Catalog #	Date

## PRODUCT OVERVIEW

GM Lighting's 120VAC 6W Mini LED Adjustable Shallow Recessed Downlight packs a lot of performance in a compact, easy to install dimmable luminaire. 3-3/4" optional white only trim ring is included with each fixture.



## FEATURES

- 120VAC
- 3000K
- ELV Dimming
- 3-1/4" dia. x 3-3/4" recess depth
- 30° adjustable gimbal
- 90+ CRI
- Up to 500 lumens
- 24°, 38°, 55° beam spreads
- 5 year warranty

## SPECIFICATIONS

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Mini-recessed extremely shallow mount with optional trim ring included.</li> <li>• 120V operation, remote power supply not required.</li> <li>• IC rated</li> <li>• Approved for damp location</li> <li>• Glass lens</li> <li>• Improved heat sink</li> <li>• 30° adjustability</li> <li>• Dimmable with standard dimmer</li> </ul> | <p><b>ELECTRICAL</b></p> <ul style="list-style-type: none"> <li>• 6W</li> <li>• 120V</li> </ul> <p><b>OPTICS</b></p> <ul style="list-style-type: none"> <li>• 3000K</li> <li>• Up to 500 lumens</li> <li>• 90+ CRI</li> </ul> <p><b>WARRANTY</b></p> <ul style="list-style-type: none"> <li>• 5-year warranty</li> </ul> |
|--|--|



## ORDERING INFORMATION

Example: GMR6-120V-IC-SP-W

Catalog No.	Dimensions	Watts	Beam Spread	Lumens	CRI	Color Temp	Finish
GMR6-120V-IC-SP-W	3-1/4" Dia. x 3-3/4" Depth	6W	24°	500	90+	3000K	W
GMR6-120V-IC-FL-W	3-1/4" Dia. x 3-3/4" Depth	6W	38°	455	90+	3000K	W
GMR6-120V-IC-WFL-W	3-1/4" Dia. x 3-3/4" Depth	6W	55°	467	90+	3000K	W
GMR6-120V-IC-SP-B	3-1/4" Dia. x 3-3/4" Depth	6W	24°	500	90+	3000K	B
GMR6-120V-IC-FL-B	3-1/4" Dia. x 3-3/4" Depth	6W	38°	455	90+	3000K	B
GMR6-120V-IC-WFL-B	3-1/4" Dia. x 3-3/4" Depth	6W	55°	467	90+	3000K	B
GMR6-120V-IC-SP-BA	3-1/4" Dia. x 3-3/4" Depth	6W	24°	500	90+	3000K	BA
GMR6-120V-IC-FL-BA	3-1/4" Dia. x 3-3/4" Depth	6W	38°	455	90+	3000K	BA
GMR6-120V-IC-WFL-BA	3-1/4" Dia. x 3-3/4" Depth	6W	55°	467	90+	3000K	BA

## ACCESSORIES

Catalog No.	Description
OTR-WH	Optional 3-3/4" trim ring - white

Note: Ambient operating temp range -4F to 104 F. Do not install in an environment that is outside of the product's listed ambient temp.