


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 58.38 lm/W			
MODEL	NMT1312	I _{max} (cd)	194.3	S/MH(C0/180)	1.26
NOMINAL POWER(W)	9.6	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	608.78	h UP,DN(C0-180)	2.6,47.1
NOMINAL FLUX(lm)	608.778	CIE CLASS	DIRECT	h UP,DN(C180-360)	2.5,47.7
LAMPS INSIDE	1	h up(%)	5.1	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	94.9	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-07-23

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	190.4	190.5	190.0	191.5	193.2	191.5	189.3	189.2	0~ 10	18.35	18.35	3.01,3.01
20	180.4	180.4	179.3	183.4	186.3	182.7	178.1	178.5	10~ 20	52.71	71.06	11.7,11.7
30	164.3	164.1	162.2	168.8	172.8	167.5	160.6	161.9	20~ 30	80.17	151.2	24.8,24.8
40	142.9	142.5	139.8	148.6	153.3	146.8	138.0	140.1	30~ 40	97.11	248.3	40.8,40.8
50	117.2	116.4	113.3	123.6	128.7	121.5	111.3	114.0	40~ 50	101.5	349.8	57.5,57.5
60	87.97	87.02	83.62	94.89	100.1	92.53	81.69	84.79	50~ 60	92.97	442.8	72.7,72.7
70	56.53	55.53	52.63	63.79	68.67	61.24	50.13	53.61	60~ 70	72.78	515.6	84.7,84.7
80	27.02	24.90	20.66	32.78	37.88	30.41	19.53	23.98	70~ 80	44.45	560.0	92,92
90	12.44	8.290	1.535	11.40	16.09	9.862	1.198	8.238	80~ 90	17.50	577.5	94.9,94.9
100	11.16	7.120	0.5744	8.422	12.01	7.622	0.4078	7.261	90~100	8.077	585.6	96.2,96.2
110	10.28	6.545	0.8148	7.040	10.98	6.901	0.7624	6.413	100~110	6.891	592.5	97.3,97.3
120	9.238	5.430	1.249	5.878	9.704	5.941	1.109	4.516	110~120	5.741	598.2	98.3,98.3
130	7.796	3.006	1.648	3.940	8.052	3.301	1.423	3.061	120~130	4.434	602.7	99,99
140	4.474	2.351	1.910	2.044	5.134	1.869	1.677	1.810	130~140	2.513	605.2	99.4,99.4
150	2.859	2.438	2.117	2.299	2.252	2.184	1.971	1.957	140~150	1.428	606.6	99.6,99.6
160	3.052	2.592	2.518	2.579	2.512	2.544	2.479	2.318	150~160	1.113	607.7	99.8,99.8
170	2.879	2.959	2.865	2.812	2.692	2.759	2.912	2.845	160~170	0.7655	608.5	100,100
180	2.772	3.199	3.186	3.186	2.792	3.186	3.220	3.186	170~180	0.2791	608.8	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	15029	7015
80	11970	9152
75	12187	10775
70	12714	11836
65	13176	12436
60	13534	12864
55	13811	13246
50	14023	13553
45	14196	13807


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.18	1.18	1.18	1.14	1.14	1.14	1.08	1.08	1.08	1.03	1.03	1.03	.97	.97	.97	.95
1.0	1.02	.97	.93	.99	.95	.91	.94	.91	.88	.89	.86	.84	.85	.83	.81	.78
2.0	.89	.81	.76	.86	.80	.74	.82	.76	.72	.78	.73	.69	.74	.70	.67	.65
3.0	.77	.69	.62	.76	.68	.62	.72	.65	.60	.68	.63	.58	.65	.60	.57	.54
4.0	.68	.60	.53	.67	.59	.52	.64	.56	.51	.61	.55	.50	.58	.53	.48	.46
5.0	.61	.52	.45	.60	.51	.45	.57	.49	.44	.54	.48	.43	.52	.46	.42	.40
6.0	.55	.46	.39	.54	.45	.39	.51	.44	.38	.49	.43	.37	.47	.41	.37	.35
7.0	.50	.41	.35	.49	.40	.34	.47	.39	.34	.45	.38	.33	.43	.37	.33	.30
8.0	.45	.37	.31	.44	.36	.31	.43	.35	.30	.41	.34	.30	.39	.34	.29	.27
9.0	.42	.33	.28	.41	.33	.27	.39	.32	.27	.38	.31	.27	.36	.31	.26	.24
10.0	.38	.30	.25	.38	.30	.25	.36	.29	.25	.35	.29	.24	.34	.28	.24	.22



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-07-23

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.323	.184	.058	.314	.179	.057	.298	.171	.055	.283	.163	.052	.269	.156	.050	
2.0	.298	.164	.050	.291	.160	.049	.276	.154	.048	.263	.148	.046	.251	.142	.045	
3.0	.274	.146	.044	.267	.143	.043	.254	.138	.042	.242	.133	.041	.231	.128	.040	
4.0	.252	.131	.038	.246	.128	.038	.234	.124	.037	.223	.120	.036	.213	.116	.035	
5.0	.232	.118	.034	.226	.116	.034	.216	.112	.033	.206	.109	.032	.197	.105	.032	
6.0	.215	.108	.031	.210	.106	.030	.200	.103	.030	.192	.100	.029	.183	.097	.029	
7.0	.199	.099	.028	.195	.097	.028	.187	.094	.027	.179	.092	.027	.171	.089	.026	
8.0	.186	.091	.026	.182	.090	.025	.174	.087	.025	.167	.085	.024	.160	.082	.024	
9.0	.174	.084	.024	.171	.083	.023	.164	.081	.023	.157	.079	.023	.151	.077	.022	
10.0	.164	.078	.022	.160	.077	.022	.154	.075	.021	.148	.073	.021	.142	.072	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.230	.230	.230	.196	.196	.196	.134	.134	.134	.077	.077	.077	.025	.025	.025	
1.0	.221	.195	.173	.189	.168	.149	.129	.115	.103	.074	.067	.060	.024	.021	.019	
2.0	.213	.172	.137	.182	.148	.118	.125	.102	.083	.072	.059	.048	.023	.019	.016	
3.0	.205	.154	.114	.176	.133	.099	.121	.092	.069	.070	.054	.041	.022	.018	.013	
4.0	.198	.141	.098	.170	.122	.085	.117	.085	.060	.067	.050	.035	.022	.016	.012	
5.0	.190	.131	.087	.163	.113	.076	.112	.079	.054	.065	.046	.032	.021	.015	.010	
6.0	.183	.123	.079	.157	.106	.069	.108	.074	.049	.063	.044	.029	.020	.014	.010	
7.0	.176	.116	.074	.151	.100	.064	.105	.070	.045	.061	.041	.027	.020	.014	.009	
8.0	.170	.110	.069	.146	.095	.060	.101	.067	.043	.059	.040	.025	.019	.013	.008	
9.0	.164	.105	.066	.141	.091	.057	.098	.064	.041	.057	.038	.024	.018	.012	.008	
10.0	.158	.101	.063	.136	.088	.055	.094	.062	.039	.055	.036	.023	.018	.012	.008	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm										
NAME: NMT1312					TYPE:			WEIGHT:		
SPEC.:NMT1312-9WW24CSN050CC0100					DIM.: 1000*13*12			SERIAL No.:		
MFR.: COLORS					SUR.:1000*13			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise				Viewed endwise				
x = 2H y = 2H	23.4	24.8	23.7	25.1	25.4	23.2	24.7	23.5	25.0	25.3
	25.0	26.3	25.3	26.6	27.0	24.7	26.1	25.1	26.4	26.7
	25.6	26.9	26.0	27.2	27.6	25.3	26.6	25.7	26.9	27.3
	26.1	27.3	26.5	27.7	28.1	25.7	26.9	26.1	27.3	27.6
	26.4	27.5	26.8	27.9	28.3	25.8	27.0	26.2	27.3	27.7
	26.6	27.7	27.0	28.1	28.5	25.8	27.0	26.3	27.3	27.8
4H	24.0	25.2	24.3	25.6	26.0	23.8	25.1	24.2	25.5	25.8
	25.7	26.9	26.2	27.2	27.7	25.5	26.7	26.0	27.0	27.5
	26.5	27.5	27.0	28.0	28.4	26.2	27.3	26.7	27.7	28.1
	27.2	28.1	27.7	28.5	29.0	26.7	27.7	27.2	28.1	28.6
	27.5	28.3	28.0	28.8	29.3	26.9	27.8	27.4	28.2	28.7
	27.7	28.5	28.2	29.0	29.5	27.0	27.8	27.5	28.2	28.8
8H	26.8	27.6	27.3	28.1	28.6	26.5	27.4	27.0	27.8	28.3
	27.6	28.3	28.1	28.8	29.3	27.2	27.9	27.7	28.4	28.9
	28.0	28.6	28.5	29.1	29.7	27.4	28.1	28.0	28.6	29.1
	28.4	28.9	29.0	29.5	30.1	27.6	28.2	28.2	28.7	29.3
12H	26.8	27.6	27.3	28.0	28.6	26.5	27.3	27.1	27.8	28.3
	27.7	28.3	28.2	28.8	29.4	27.3	27.9	27.8	28.4	29.0
	28.1	28.6	28.7	29.2	29.8	27.6	28.1	28.1	28.6	29.2
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.2				+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3				+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3				+ 0.1 / - 0.3					

CIE Pub.117, 608.8 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.7)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	55	43	36	54	43	36	53	42	36	29
0.80	65	53	46	64	53	45	62	52	45	38
1.00	73	62	54	72	61	54	69	62	53	46
1.25	80	69	62	79	68	61	75	67	60	52
1.50	85	75	68	83	74	67	80	72	66	57
2.00	92	83	76	90	82	75	86	79	74	65
2.50	96	88	82	94	86	80	89	83	78	69
3.00	100	92	87	97	91	85	92	87	82	73
4.00	104	98	93	101	96	91	96	92	88	77
5.00	107	101	97	104	99	95	98	95	91	80
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

Flux out:407.4 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-07-23

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	14288
L_0~180(75)av	13961
L_0~180(85)av	18477
L_90~270(65)av	12227
L_90~270(75)av	10493
L_90~270(85)av	6822
L_45(65)av	13530
L_45(75)av	12731
L_45(85)av	14061

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-07-23

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.4345A P:10.43W PF:1.000 Freq:0Hz Lamp Flux:608.778x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-9WW24CSN050CC0100	DIM.: 1000*13*12	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	194	194	193	193	194	194	193	193										
5	193	193	193	193	194	193	192	192										
10	190	190	190	191	193	192	189	189										
15	186	186	186	188	191	188	185	185										
20	180	180	179	183	186	183	178	179										
25	173	173	172	177	180	176	170	171										
30	164	164	162	169	173	168	161	162										
35	154	154	152	159	164	158	150	152										
40	143	142	140	149	153	147	138	140										
45	130	130	127	137	142	135	125	127										
50	117	116	113	124	129	121	111	114										
55	103	102	98.8	110	115	107	96.8	99.7										
60	88.0	87.0	83.6	94.9	100	92.5	81.7	84.8										
65	72.4	71.4	68.3	79.5	84.6	77.0	66.0	69.3										
70	56.5	55.5	52.6	63.8	68.7	61.2	50.1	53.6										
75	41.0	39.6	36.3	48.1	52.9	45.4	34.4	38.2										
80	27.0	24.9	20.7	32.8	37.9	30.4	19.5	24.0										
85	17.0	13.5	7.95	19.5	24.8	17.5	7.51	13.1										
90	12.4	8.29	1.53	11.4	16.1	9.86	1.20	8.24										
95	11.6	7.47	1.40	9.19	12.7	7.97	0.30	7.52										
100	11.2	7.12	0.57	8.42	12.0	7.62	0.41	7.26										
105	10.7	6.83	0.62	7.65	11.5	7.30	0.58	6.91										
110	10.3	6.54	0.81	7.04	11.0	6.90	0.76	6.41										
115	9.80	5.78	1.04	6.56	10.4	6.46	0.93	5.30										
120	9.24	5.43	1.25	5.88	9.70	5.94	1.11	4.52										
125	8.50	5.02	1.47	5.64	8.84	5.56	1.26	4.13										
130	7.80	3.01	1.65	3.94	8.05	3.30	1.42	3.06										
135	7.05	2.25	1.78	1.94	7.22	1.74	1.55	1.88										
140	4.47	2.35	1.91	2.04	5.13	1.87	1.68	1.81										
145	2.82	2.40	2.01	2.18	2.18	2.02	1.80	1.89										
150	2.86	2.44	2.12	2.30	2.25	2.18	1.97	1.96										
155	2.97	2.48	2.29	2.45	2.40	2.37	2.21	2.10										
160	3.05	2.59	2.52	2.58	2.51	2.54	2.48	2.32										
165	3.07	2.76	2.70	2.69	2.63	2.63	2.71	2.57										
170	2.88	2.96	2.87	2.81	2.69	2.76	2.91	2.85										
175	2.74	3.13	3.07	2.99	2.68	2.97	3.09	3.07										
180	2.77	3.20	3.19	3.19	2.79	3.19	3.22	3.19										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: