


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.59lx1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 17.05 lm/W			
MODEL	NMT1312	I <sub>max</sub> (cd)	47.52	S/MH(C0/180)	1.31
NOMINAL POWER(W)	8	LOR(%)	100.0	S/MH(C90/270)	1.26
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	146.59	h UP,DN(C0-180)	1.2,47.3
NOMINAL FLUX(lm)	146.591	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.9,49.6
LAMPS INSIDE	1	h up(%)	3.1	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	96.9	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:COLORS  
 Test Date:2019-04-04

Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:7.500m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C90	C180	C270					g	F zone	F total	%lum,lamp
10	46.52	46.22	47.11	46.18					0~ 10	4.475	4.475	3.05,3.05
20	44.08	43.81	45.21	43.67					10~ 20	12.86	17.33	11.8,11.8
30	40.26	39.91	41.79	39.73					20~ 30	19.58	36.91	25.2,25.2
40	35.19	34.72	37.03	34.54					30~ 40	23.80	60.71	41.4,41.4
50	29.00	28.47	31.07	28.35					40~ 50	25.01	85.72	58.5,58.5
60	21.85	21.55	24.28	21.32					50~ 60	23.10	108.8	74.2,74.2
70	14.03	13.68	16.66	13.72					60~ 70	18.26	127.1	86.7,86.7
80	6.369	5.425	8.801	5.956					70~ 80	11.12	138.2	94.3,94.3
90	1.714	0.1762	3.073	0.8107					80~ 90	3.912	142.1	96.9,96.9
100	1.451	0.0188	2.300	0.0534					90~100	1.195	143.3	97.8,97.8
110	1.310	0.0471	2.043	0.0501					100~110	0.9607	144.3	98.4,98.4
120	1.159	0.0846	1.755	0.0940					110~120	0.8133	145.1	99,99
130	0.9370	0.1097	1.444	0.1127					120~130	0.6437	145.7	99.4,99.4
140	0.6644	0.1473	1.047	0.1430					130~140	0.4401	146.2	99.7,99.7
150	0.2948	0.1755	0.5283	0.1817					140~150	0.2561	146.4	99.9,99.9
160	0.2180	0.1975	0.2090	0.1922					150~160	0.1053	146.5	99.9,99.9
170	0.2170	0.2110	0.2059	0.1934					160~170	0.0585	146.6	100,100
180	0.2162	0.2099	0.2037	0.1943					170~180	0.0197	146.6	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-04-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.59lx1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	2923	1832
80	2821	2403
75	2996	2865
70	3156	3076
65	3275	3219
60	3362	3316
55	3424	3378
50	3471	3407
45	3506	3450


C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-04-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.59lx1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.04	1.04	1.04	.99	.99	.99	.97
1.0	1.02	.98	.94	.90	.96	.92	.95	.92	.89	.91	.88	.85	.86	.84	.82	.80
2.0	.89	.82	.76	.87	.80	.75	.83	.77	.73	.79	.74	.70	.75	.72	.68	.66
3.0	.78	.69	.63	.76	.68	.62	.72	.66	.60	.69	.64	.59	.66	.62	.58	.55
4.0	.69	.60	.53	.67	.59	.52	.64	.57	.51	.62	.55	.50	.59	.54	.49	.47
5.0	.61	.52	.45	.60	.51	.45	.57	.50	.44	.55	.49	.43	.53	.47	.43	.40
6.0	.55	.46	.39	.54	.45	.39	.52	.44	.39	.50	.43	.38	.48	.42	.37	.35
7.0	.50	.41	.35	.49	.40	.34	.47	.39	.34	.45	.39	.34	.44	.38	.33	.31
8.0	.45	.37	.31	.45	.36	.31	.43	.36	.30	.41	.35	.30	.40	.34	.30	.28
9.0	.42	.33	.28	.41	.33	.28	.40	.32	.27	.38	.32	.27	.37	.31	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.35	.29	.24	.34	.28	.24	.22



C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:COLORS  
 Test Date:2019-04-04

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:7.500m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.591x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.323	.184	.058	.315	.180	.057	.300	.172	.055	.286	.165	.053	.273	.158	.051	
2.0	.300	.164	.050	.293	.161	.050	.279	.155	.048	.267	.150	.047	.255	.144	.046	
3.0	.275	.147	.044	.269	.144	.043	.257	.139	.042	.246	.135	.041	.236	.131	.040	
4.0	.253	.132	.039	.247	.130	.038	.237	.126	.038	.227	.122	.037	.218	.118	.036	
5.0	.233	.119	.034	.228	.117	.034	.219	.114	.034	.210	.111	.033	.202	.108	.032	
6.0	.216	.108	.031	.211	.107	.031	.203	.104	.030	.195	.101	.030	.187	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.095	.027	.182	.093	.027	.175	.091	.027	
8.0	.187	.091	.026	.183	.090	.026	.176	.088	.025	.170	.086	.025	.164	.084	.025	
9.0	.175	.085	.024	.172	.084	.023	.165	.082	.023	.160	.080	.023	.154	.078	.023	
10.0	.164	.079	.022	.161	.078	.022	.156	.076	.021	.150	.075	.021	.145	.073	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.214	.214	.214	.183	.183	.183	.125	.125	.125	.072	.072	.072	.023	.023	.023	
1.0	.205	.180	.157	.175	.154	.135	.120	.106	.093	.069	.061	.054	.022	.020	.018	
2.0	.197	.156	.121	.169	.134	.104	.116	.093	.073	.067	.054	.043	.021	.017	.014	
3.0	.189	.138	.097	.162	.119	.084	.111	.083	.059	.064	.048	.035	.021	.016	.011	
4.0	.182	.125	.082	.156	.108	.071	.107	.075	.050	.062	.044	.030	.020	.014	.010	
5.0	.174	.115	.071	.150	.099	.062	.103	.069	.043	.060	.041	.026	.019	.013	.008	
6.0	.167	.106	.063	.144	.092	.055	.099	.065	.039	.057	.038	.023	.019	.012	.008	
7.0	.160	.100	.057	.138	.086	.050	.095	.061	.035	.055	.036	.021	.018	.012	.007	
8.0	.154	.094	.053	.132	.081	.046	.092	.057	.033	.053	.034	.019	.017	.011	.006	
9.0	.148	.089	.049	.127	.077	.043	.088	.054	.031	.051	.032	.018	.017	.011	.006	
10.0	.142	.085	.047	.122	.074	.041	.085	.052	.029	.049	.031	.017	.016	.010	.006	

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-04-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.59lx1 lm											
NAME: NMT1312					TYPE:			WEIGHT:			
SPEC.:NMT1312-OR24NSN050CC0100-PLus					DIM.: 1000*13*12			SERIAL No.:			
MFR.: Colors					SUR.:1000*13*12			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	23.6	25.1	23.9	25.4	25.6	23.6	25.1	23.9	25.3	25.6	
	3H	25.2	26.6	25.6	26.9	27.2	25.1	26.5	25.5	26.8	27.1
	4H	25.9	27.2	26.2	27.5	27.8	25.8	27.1	26.1	27.4	27.7
	6H	26.4	27.6	26.7	27.9	28.3	26.2	27.4	26.5	27.7	28.1
	8H	26.5	27.7	26.9	28.1	28.4	26.3	27.5	26.7	27.8	28.2
	12H	26.7	27.8	27.1	28.2	28.5	26.3	27.5	26.7	27.8	28.2
4H	2H	24.2	25.5	24.6	25.9	26.2	24.2	25.5	24.5	25.8	26.1
	3H	26.0	27.2	26.4	27.5	27.9	25.9	27.1	26.3	27.4	27.8
	4H	26.8	27.8	27.2	28.2	28.6	26.7	27.7	27.1	28.1	28.5
	6H	27.4	28.3	27.9	28.8	29.2	27.2	28.2	27.7	28.6	29.0
	8H	27.6	28.5	28.1	28.9	29.4	27.4	28.2	27.8	28.7	29.1
	12H	27.8	28.6	28.3	29.1	29.5	27.5	28.3	27.9	28.7	29.2
8H	4H	27.1	27.9	27.5	28.4	28.8	27.0	27.8	27.4	28.3	28.7
	6H	27.8	28.6	28.3	29.0	29.5	27.6	28.4	28.1	28.8	29.3
	8H	28.1	28.8	28.7	29.3	29.8	27.9	28.5	28.4	29.0	29.5
	12H	28.4	29.0	29.0	29.5	30.0	28.0	28.6	28.6	29.1	29.6
12H	4H	27.1	27.9	27.5	28.3	28.8	27.0	27.8	27.5	28.2	28.7
	6H	27.9	28.5	28.4	29.0	29.5	27.7	28.3	28.2	28.8	29.3
	8H	28.2	28.8	28.8	29.3	29.8	28.0	28.5	28.5	29.0	29.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 146.6 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -6.7)

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-04-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.59lx1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	44	37	53	43	36	30
0.80	65	54	46	64	53	46	62	52	45	38
1.00	74	62	55	72	62	54	70	63	54	46
1.25	81	70	63	79	69	62	76	68	61	53
1.50	86	76	68	84	75	68	81	73	66	58
2.00	93	84	77	91	83	76	87	80	75	66
2.50	97	89	82	95	87	81	90	84	79	70
3.00	100	93	87	98	91	86	94	88	84	74
4.00	105	99	94	102	97	92	97	93	89	79
5.00	107	102	98	104	100	96	99	96	92	82
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-04-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.59lx1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: COLORS  
Test Date: 2019-04-04


Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 7.500m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.59lx1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:

Flux out:102.3 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-04-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## ISOLUX DIAGRAM

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.59lx1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: COLORS  
 Test Date: 2019-04-04

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity: 65.0%  
 Test Distance: 7.500m [K=1.0000]  
 Remarks:

## LED Avg.L Report

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.59lx1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	3509
L_0~180(75)av	3380
L_0~180(85)av	3842
L_90~270(65)av	3216
L_90~270(75)av	2876
L_90~270(85)av	2111
L_45(65)av	3341
L_45(75)av	3089
L_45(85)av	2818

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:COLORS  
 Test Date:2019-04-04

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:7.500m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: COLORS  
Test Date: 2019-04-04

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 7.500m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3590A P:8.600W PF:0 Freq:0Hz Lamp Flux:146.591x1 lm		
NAME: NMT1312	TYPE:	WEIGHT:
SPEC.:NMT1312-OR24NSN050CC0100-PLus	DIM.: 1000*13*12	SERIAL No.:
MFR.: Colors	SUR.:1000*13*12	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	90	180	270															
0	47.5	47.0	47.5	47.0															
5	47.2	46.8	47.5	46.8															
10	46.5	46.2	47.1	46.2															
15	45.5	45.2	46.4	45.1															
20	44.1	43.8	45.2	43.7															
25	42.3	42.0	43.7	41.9															
30	40.3	39.9	41.8	39.7															
35	37.9	37.5	39.6	37.3															
40	35.2	34.7	37.0	34.5															
45	32.2	31.7	34.2	31.5															
50	29.0	28.5	31.1	28.4															
55	25.5	25.2	27.8	24.9															
60	21.9	21.6	24.3	21.3															
65	18.0	17.7	20.6	17.7															
70	14.0	13.7	16.7	13.7															
75	10.1	9.64	12.7	9.71															
80	6.37	5.42	8.80	5.96															
85	3.31	2.08	5.40	2.71															
90	1.71	0.18	3.07	0.81															
95	1.52	0.02	2.44	0.22															
100	1.45	0.02	2.30	0.05															
105	1.38	0.03	2.15	0.05															
110	1.31	0.05	2.04	0.05															
115	1.24	0.06	1.90	0.05															
120	1.16	0.08	1.75	0.09															
125	1.07	0.09	1.62	0.09															
130	0.94	0.11	1.44	0.11															
135	0.81	0.13	1.15	0.14															
140	0.66	0.15	1.05	0.14															
145	0.50	0.16	0.81	0.15															
150	0.29	0.18	0.53	0.18															
155	0.22	0.18	0.23	0.19															
160	0.22	0.20	0.21	0.19															
165	0.22	0.21	0.21	0.19															
170	0.22	0.21	0.21	0.19															
175	0.22	0.21	0.20	0.19															
180	0.22	0.21	0.20	0.19															

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-04-04

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks: