LEDTASK™ 24VDC HIGH DENSITY FLEXIBLE SO LED TAPE



PRODUCT DESCRIPTION

GM Lighting's LEDTask 24VDC High Density Standard Output Flexible LED Tape features a tightly arranged diode placement that produces an even, high output light. The intense, even light output is perfect for areas that demand a strong and energy efficient light source. Available in 2700K, 3000K, 3500K or 4000K.

Custom lengths available - consult factory











KEY FEATURES

- · Low profile, high density diode placement that creates a diode-free line of light
- Flexible standard output (SO) LED tape that is cuttable in the field (cuttable every 7 diodes or 1")
- Mounts with 3M VHB[™] double stick tape
- Flexible tape to tape and tape to power supply connectors available (see below).
- · Dimmable. See www.gmlighting.net
- Maximum run on a given lead is 32'
- · Shipped in anti-static packaging
- Available in 16'-4" (5M) reels.

ELECTRICAL

- 24VDC remote power supply required
- Rated at 2.5W per foot
- 120° viewing angle
- 50.000 hr. operation

OPTICS

- 2700K, 3000K, 3500K, 4000K
- · Up to 238 lumens per foot.

CERTIFICATION

• ETL • Class 2

WARRANTY

5 year warranty

POWER SUPPLIES

 For a complete list of applicable 24VDC power supplies, please see our website at www.gmlighting.net


ORDERING MATRIX

Catalog No.	Length	Wattage	Lumens	CRI	Color Temp.*	Mounting Channels
HDT-28024-S0-27	16'-4" / 5M	2.5W/ft.	215	90+	2700K	This LED Tape will fit into the following mounting channels: LED-CHL-45-1200 LED-CHL-XD LED-CHL-XD-F LED-CHL-BND-4/8
HDT-28024-S0-30	16'-4" / 5M	2.5W/ft.	220	90+	3000K	
HDT-28024-S0-35	16'-4" / 5M	2.5W/ft.	228	90+	3500K	
HDT-28024-S0-40	16'-4" / 5M	2.5W/ft.	238	90+	4000K	
Each 16'-4" (5M) reel includes: (3) ESTW-60 connectors and 24" of lead affixed at start of reel.						


^{*} Kelvin temperature (color) ±200K

CONNECTORS AND ACCESSORIES

Cat. No.	Description
ESTC-1	Sure-Tite tape to tape connector
ESTLK-60	Sure-Tite 60" tape to tape connector
ESTW-60	Sure-Tite 60" tape to power connector



CONNECTOR DIAGRAMS



©2018 GM Lighting Specifications are subject to change

9830 W. 190th Street, Unit F Mokena, IL 60448

Toll-Free: (866) 671-0811 FAX: (708) 478-2640

www.gmlighting.net sales@gmlighting.net



HDT-28024-SO_032018