

MicroTask

120V Mini IC Rated Round Adjustable Gimbal LED Downlight



Project Name	Type
--------------	------

Catalog #	Date
-----------	------

PRODUCT OVERVIEW

Excellent color rendition and high lumens in a 3" mini-adjustable, IC rated, damp location, round trim downlight that features an inline junction box connected by a modular twist-connector. 360° rotation, 30° tilt on axis for precise beam control. Perfect for wall wash or focus aiming applications. Available in 2700K or 3000K color temp and white semi-gloss finish. Flexible modular extenders available. Extenders available. See below.



FEATURES

- 3-3/8" trim diameter, 1-1/2" recess depth
- Dimmable
- Up to 550 lumens
- 90+ CRI
- IC rated (ceiling clearance required: 1-1/2" for Romex, 3-1/2" for MC or BX installations)
- Adjustable gimbal (360° rotation - 30° tilt on axis)
- Die-cast construction
- Quick and easy installation
- In-line junction box connected by 12" TwistLock cable
- Snap-in spring clips installation
- Shallow mount

SPECIFICATIONS

ELECTRICAL

- 120V
- 8W

OPTICS

- 2700K, 3000K
- 30° beam angle

LABEL

- ETL
- Title 24
- Energy Star

WARRANTY

- 5 years



CUT-OUT DIMENSIONS

MDL-3AR: 2.75"

Ordering Example:

MDL-3AR-30-WH

ORDERING INFORMATION

<input type="text"/>	-	<input type="text"/>	-	<input type="text"/>
----------------------	---	----------------------	---	----------------------

Model	-	Color Temp.	Finish
MDL-3AR		27 (2700K)	WH (WHITE)
		30 (3000K)	

CONNECTORS AND ACCESSORIES

Catalog No.	Description
MDL-5FT-EXT	5' EXTENSION CORD FOR MDL SERIES DOWNLIGHTS
MDL-10FT-EXT	10' EXTENSION CORD FOR MDL SERIES DOWNLIGHTS
MDL-20FT-EXT	20' EXTENSION CORD FOR MDL SERIES DOWNLIGHTS
UNV-NCP	NEW CONSTRUCTION PLATE FOR ALL RSD SERIES DOWNLIGHTS

MicroTask

120V Mini IC Rated Round Adjustable Gimbal LED Downlight



Catalog No.	Recess Depth	Trim Diameter	Wattage	Lumens	CRI	Color Temp.
MDL-3AR-27-WH	1-1/2"	3-3/8"	8W	545	90+	2700K
MDL-3AR-30-WH				550		3000K

