


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 45.83 lm/W			
MODEL	NM1217	I _{max} (cd)	150.3	S/MH(C0/180)	1.34
NOMINAL POWER(W)	9.6	LOR(%)	100.0	S/MH(C90/270)	1.25
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	480.22	h UP,DN(C0-180)	3.1,49.1
NOMINAL FLUX(lm)	480.215	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.8,45.9
LAMPS INSIDE	1	h up(%)	4.9	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	95.1	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-07-23

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	148.9	148.9	146.7	145.8	147.1	146.7	146.7	147.6	0- 10	14.18	14.18	2.95,2.95
20	144.1	142.9	138.5	137.7	139.6	138.5	138.5	141.4	10- 20	40.74	54.92	11.4,11.4
30	134.7	132.5	125.7	125.0	127.0	125.7	125.4	130.8	20- 30	62.14	117.1	24.4,24.4
40	121.5	118.2	108.8	108.3	110.1	108.5	108.2	116.0	30- 40	75.61	192.7	40.1,40.1
50	105.4	100.4	88.71	88.08	89.77	88.02	87.38	97.11	40- 50	79.56	272.2	56.7,56.7
60	85.88	78.89	66.11	65.22	66.93	64.95	63.80	75.58	50- 60	73.61	345.8	72,72
70	62.05	55.65	41.93	40.78	42.99	40.38	38.68	51.28	60- 70	58.32	404.2	84.2,84.2
80	37.70	32.06	17.40	17.32	20.30	17.18	14.63	27.42	70- 80	36.46	440.6	91.8,91.8
90	22.82	17.16	1.890	3.965	6.547	4.526	0.9570	12.76	80- 90	15.84	456.5	95.1,95.1
100	20.26	14.95	0.7486	2.571	4.381	3.313	0.4208	10.33	90-100	8.391	464.9	96.8,96.8
110	6.020	8.357	0.8277	2.042	4.187	3.126	0.5280	3.844	100-110	5.873	470.7	98,98
120	4.088	3.040	1.155	1.703	3.914	2.433	0.7956	1.944	110-120	2.741	473.5	98.6,98.6
130	3.788	2.745	1.489	1.509	3.179	2.258	1.062	1.917	120-130	2.119	475.6	99,99
140	3.427	2.431	1.616	1.590	2.872	1.737	1.290	1.743	130-140	1.685	477.3	99.4,99.4
150	2.607	1.977	1.703	1.743	2.091	1.763	1.497	1.737	140-150	1.254	478.5	99.6,99.6
160	2.378	2.004	1.943	1.877	2.104	1.956	1.811	1.910	150-160	0.8952	479.4	99.8,99.8
170	2.251	2.151	2.204	2.057	2.050	2.090	2.138	2.124	160-170	0.5862	480.0	100,100
180	2.071	2.451	2.438	2.378	2.104	2.338	2.465	2.324	170-180	0.2086	480.2	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.08	1.08	1.08	1.03	1.03	1.03	.97	.97	.97	.95
1.0	1.02	.97	.93	.99	.95	.91	.94	.90	.87	.89	.86	.84	.85	.82	.80	.78
2.0	.88	.81	.75	.86	.79	.74	.81	.76	.71	.77	.73	.69	.74	.70	.67	.64
3.0	.77	.69	.62	.75	.67	.61	.71	.65	.59	.68	.62	.58	.65	.60	.56	.54
4.0	.68	.59	.52	.66	.58	.52	.63	.56	.50	.60	.54	.49	.58	.52	.48	.45
5.0	.61	.51	.45	.59	.51	.44	.57	.49	.43	.54	.47	.42	.52	.46	.41	.39
6.0	.55	.45	.39	.53	.45	.38	.51	.43	.38	.49	.42	.37	.47	.41	.36	.34
7.0	.49	.40	.34	.48	.40	.34	.46	.39	.33	.44	.38	.33	.43	.37	.32	.30
8.0	.45	.36	.30	.44	.36	.30	.42	.35	.30	.41	.34	.29	.39	.33	.29	.27
9.0	.41	.33	.27	.40	.32	.27	.39	.32	.27	.37	.31	.26	.36	.30	.26	.24
10.0	.38	.30	.25	.37	.30	.25	.36	.29	.24	.35	.28	.24	.33	.28	.23	.22



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

rcc	80%	70%	50%	30%	10%	0
rw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
rfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)					
0.0						
1.0	.329 .187 .059	.321 .183 .058	.304 .175 .056	.290 .167 .054	.276 .160 .052	
2.0	.303 .166 .051	.295 .162 .050	.281 .156 .048	.267 .150 .047	.255 .144 .045	
3.0	.277 .147 .044	.270 .145 .044	.257 .139 .042	.245 .134 .041	.234 .130 .040	
4.0	.254 .132 .039	.248 .130 .038	.236 .125 .037	.226 .121 .037	.216 .117 .036	
5.0	.234 .119 .034	.228 .117 .034	.218 .113 .033	.208 .110 .033	.199 .107 .032	
6.0	.216 .108 .031	.211 .107 .031	.202 .103 .030	.193 .100 .030	.185 .097 .029	
7.0	.201 .099 .028	.196 .098 .028	.188 .095 .027	.180 .092 .027	.173 .090 .026	
8.0	.187 .091 .026	.183 .090 .025	.175 .088 .025	.168 .085 .025	.162 .083 .024	
9.0	.175 .085 .024	.171 .084 .023	.164 .081 .023	.158 .079 .023	.152 .077 .022	
10.0	.164 .079 .022	.161 .078 .022	.155 .076 .021	.149 .074 .021	.143 .072 .021	

rcc	80%	70%	50%	30%	10%	0
rw	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	50% 30% 10%	0
rfc	20%	20%	20%	20%	20%	0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)					
0.0	.228 .228 .228	.195 .195 .195	.133 .133 .133	.076 .076 .076	.024 .024 .024	
1.0	.220 .194 .171	.188 .166 .147	.129 .115 .102	.074 .066 .059	.024 .021 .019	
2.0	.212 .170 .135	.182 .146 .117	.124 .101 .081	.072 .059 .048	.023 .019 .016	
3.0	.204 .153 .112	.175 .132 .097	.120 .092 .068	.069 .053 .040	.022 .017 .013	
4.0	.197 .140 .096	.169 .121 .084	.116 .084 .059	.067 .049 .035	.022 .016 .011	
5.0	.189 .129 .085	.162 .112 .074	.112 .078 .052	.065 .046 .031	.021 .015 .010	
6.0	.182 .121 .078	.156 .105 .068	.108 .073 .048	.063 .043 .028	.020 .014 .009	
7.0	.175 .114 .072	.151 .099 .063	.104 .070 .044	.060 .041 .026	.020 .013 .009	
8.0	.169 .109 .068	.145 .094 .059	.100 .066 .042	.058 .039 .025	.019 .013 .008	
9.0	.162 .104 .064	.140 .090 .056	.097 .063 .040	.056 .037 .024	.018 .012 .008	
10.0	.157 .100 .062	.135 .086 .054	.094 .061 .038	.055 .036 .023	.018 .012 .008	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm											
NAME: NMS1217					TYPE:			WEIGHT:			
SPEC.:NMS1217-9WW24CSN050CC0100					DIM.: 1000*12*17			SERIAL No.:			
MFR.: COLORS					SUR.:1000*12			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	24.7	26.2	25.1	26.5	26.8	23.8	25.3	24.2	25.6	25.9	
	26.7	28.1	27.1	28.4	28.7	25.4	26.7	25.7	27.1	27.4	
	27.6	28.9	28.0	29.3	29.7	26.0	27.3	26.4	27.6	28.0	
	28.5	29.8	28.9	30.1	30.5	26.5	27.7	26.9	28.0	28.4	
	29.0	30.2	29.4	30.5	30.9	26.6	27.8	27.0	28.1	28.5	
	29.5	30.6	29.9	31.0	31.4	26.7	27.8	27.1	28.2	28.6	
4H	2H	25.3	26.6	25.7	27.0	27.3	24.7	26.0	25.0	26.3	26.7
	3H	27.5	28.7	28.0	29.0	29.5	26.4	27.6	26.9	28.0	28.4
	4H	28.6	29.6	29.1	30.1	30.5	27.2	28.3	27.7	28.7	29.1
	6H	29.7	30.6	30.2	31.0	31.5	27.8	28.7	28.3	29.2	29.7
	8H	30.2	31.1	30.7	31.5	32.0	28.0	28.9	28.5	29.3	29.8
	12H	30.8	31.6	31.3	32.1	32.6	28.2	28.9	28.7	29.4	29.9
8H	4H	28.9	29.8	29.4	30.2	30.7	27.8	28.6	28.2	29.1	29.6
	6H	30.2	30.9	30.7	31.4	32.0	28.6	29.3	29.1	29.8	30.3
	8H	30.9	31.6	31.5	32.1	32.6	28.9	29.6	29.5	30.1	30.6
	12H	31.7	32.3	32.3	32.8	33.4	29.2	29.8	29.8	30.3	30.9
12H	4H	29.0	29.7	29.5	30.2	30.7	27.9	28.6	28.4	29.1	29.6
	6H	30.3	31.0	30.9	31.5	32.0	28.8	29.4	29.3	30.0	30.5
	8H	31.1	31.7	31.7	32.2	32.8	29.2	29.8	29.8	30.3	30.9
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.5					

CIE Pub.117, 480.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.5)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	55	43	36	54	43	36	53	42	35	29
0.80	65	53	45	63	52	45	61	51	44	37
1.00	73	61	54	71	60	53	69	62	53	45
1.25	80	69	61	78	68	61	75	66	60	52
1.50	85	74	67	83	73	66	79	71	65	57
2.00	92	83	76	90	81	75	86	79	73	64
2.50	96	88	81	94	86	80	89	83	78	68
3.00	99	92	86	97	90	85	92	87	82	72
4.00	104	97	92	101	95	91	96	91	87	77
5.00	106	101	96	103	99	94	98	94	91	80
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Flux out:317.7 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	12771
L_0~180(75)av	12944
L_0~180(85)av	19085
L_90~270(65)av	10414
L_90~270(75)av	8985
L_90~270(85)av	6072
L_45(65)av	11662
L_45(75)av	11200
L_45(85)av	13856

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-07-23

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.4366A P:10.48W PF:1.000 Freq:0Hz Lamp Flux:480.215x1 lm		
NAME: NMS1217	TYPE:	WEIGHT:
SPEC.:NMS1217-9WW24CSN050CC0100	DIM.: 1000*12*17	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	150	150	150	149	150	150	150	149										
5	150	150	149	148	149	149	149	149										
10	149	149	147	146	147	147	147	148										
15	147	146	143	142	144	143	143	145										
20	144	143	139	138	140	139	138	141										
25	140	138	133	132	134	133	132	137										
30	135	132	126	125	127	126	125	131										
35	128	126	118	117	119	118	117	124										
40	122	118	109	108	110	109	108	116										
45	114	110	99.1	98.6	100	98.6	98.1	107										
50	105	100	88.7	88.1	89.8	88.0	87.4	97.1										
55	96.2	90.3	77.7	76.9	78.6	76.7	75.9	86.6										
60	85.9	78.9	66.1	65.2	66.9	64.9	63.8	75.6										
65	74.6	67.1	54.2	53.1	54.9	52.7	51.4	63.7										
70	62.0	55.7	41.9	40.8	43.0	40.4	38.7	51.3										
75	49.2	43.5	29.5	28.6	31.2	28.3	26.3	38.8										
80	37.7	32.1	17.4	17.3	20.3	17.2	14.6	27.4										
85	28.4	22.8	7.26	8.50	11.5	8.61	5.44	18.1										
90	22.8	17.2	1.89	3.97	6.55	4.53	0.96	12.8										
95	20.9	15.5	1.10	2.89	4.81	3.48	0.56	11.4										
100	20.3	15.0	0.75	2.57	4.38	3.31	0.42	10.3										
105	19.3	13.0	0.73	2.43	4.29	3.22	0.41	4.04										
110	6.02	8.36	0.83	2.04	4.19	3.13	0.53	3.84										
115	4.26	5.39	1.03	1.70	4.14	2.89	0.66	1.94										
120	4.09	3.04	1.16	1.70	3.91	2.43	0.80	1.94										
125	3.93	3.23	1.37	1.69	3.51	2.30	0.93	1.94										
130	3.79	2.74	1.49	1.51	3.18	2.26	1.06	1.92										
135	3.62	2.62	1.57	1.52	3.09	2.02	1.18	1.84										
140	3.43	2.43	1.62	1.59	2.87	1.74	1.29	1.74										
145	3.13	2.04	1.70	1.66	2.58	1.70	1.40	1.74										
150	2.61	1.98	1.70	1.74	2.09	1.76	1.50	1.74										
155	2.49	1.98	1.80	1.82	2.10	1.87	1.65	1.79										
160	2.38	2.00	1.94	1.88	2.10	1.96	1.81	1.91										
165	2.41	2.06	2.09	1.95	2.10	2.01	1.98	2.02										
170	2.25	2.15	2.20	2.06	2.05	2.09	2.14	2.12										
175	2.08	2.29	2.33	2.18	2.01	2.19	2.31	2.26										
180	2.07	2.45	2.44	2.38	2.10	2.34	2.46	2.32										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-23

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: