


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 20.30 lm/W			
MODEL	NMS1217-Plus	I _{max} (cd)	67.31	S/MH(C0/180)	1.31
NOMINAL POWER(W)	9.6	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	208.75	h UP,DN(C0-180)	2.6,48.1
NOMINAL FLUX(lm)	208.747	CIE CLASS	DIRECT	h UP,DN(C180-360)	2.5,46.7
LAMPS INSIDE	1	h up(%)	5.1	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	94.9	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	66.75	66.34	65.59	65.29	65.80	65.38	65.31	65.80	0- 10	6.333	6.333	3.03,3.03
20	64.15	63.59	61.93	61.66	62.18	61.52	61.49	62.68	10- 20	18.17	24.50	11.7,11.7
30	59.20	58.61	56.13	55.64	56.55	55.71	55.45	57.47	20- 30	27.60	52.10	25,25
40	52.27	51.51	48.44	48.25	49.16	48.18	47.70	50.23	30- 40	33.38	85.48	41,41
50	43.48	42.73	39.25	39.44	40.40	39.22	38.54	41.33	40- 50	34.85	120.3	57.6,57.6
60	33.23	32.62	28.85	29.49	30.49	29.23	28.30	31.23	50- 60	31.83	152.2	72.9,72.9
70	22.15	21.56	17.76	18.76	19.81	18.65	17.52	20.38	60- 70	24.78	176.9	84.8,84.8
80	11.55	10.76	7.012	8.523	9.864	8.735	7.267	10.04	70- 80	15.04	192.0	92,92
90	4.864	3.721	0.5137	3.066	4.418	3.536	0.9208	3.544	80- 90	6.046	198.0	94.9,94.9
100	4.002	2.852	0.2219	2.411	3.627	2.880	0.1472	2.471	90-100	2.841	200.9	96.2,96.2
110	3.728	2.444	0.2726	2.044	3.306	2.465	0.2885	2.292	100-110	2.365	203.2	97.4,97.4
120	3.340	1.561	0.4073	1.616	2.850	1.791	0.4276	1.483	110-120	1.873	205.1	98.3,98.3
130	2.325	1.296	0.5343	1.349	2.330	1.523	0.5477	1.156	120-130	1.372	206.5	98.9,98.9
140	1.845	0.8605	0.6516	0.7748	1.776	0.7741	0.6345	0.7884	130-140	0.9436	207.4	99.4,99.4
150	1.069	0.7748	0.7281	0.8819	0.8416	0.8282	0.7282	0.6880	140-150	0.5767	208.0	99.6,99.6
160	0.9826	0.8349	0.8549	0.9819	0.8582	0.9494	0.8885	0.7280	150-160	0.3895	208.4	99.8,99.8
170	0.9704	0.9687	1.021	1.062	0.8646	0.9885	1.042	0.9427	160-170	0.2620	208.6	100,100
180	0.9618	1.122	1.156	1.156	0.9552	1.122	1.169	1.162	170-180	0.0974	208.7	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	7051	2682
80	5542	3365
75	5369	3932
70	5397	4326
65	5472	4608
60	5538	4809
55	5593	4964
50	5637	5089
45	5666	5190


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.18	1.18	1.18	1.14	1.14	1.14	1.08	1.08	1.08	1.03	1.03	1.03	.97	.97	.97	.95
1.0	1.02	.98	.93	.99	.95	.91	.94	.91	.88	.89	.87	.84	.85	.83	.81	.78
2.0	.89	.82	.76	.86	.80	.74	.82	.76	.72	.78	.73	.69	.74	.70	.67	.65
3.0	.78	.69	.63	.76	.68	.62	.72	.65	.60	.68	.63	.58	.65	.61	.57	.54
4.0	.69	.60	.53	.67	.59	.52	.64	.57	.51	.61	.55	.50	.58	.53	.48	.46
5.0	.61	.52	.45	.60	.51	.45	.57	.50	.44	.54	.48	.43	.52	.47	.42	.40
6.0	.55	.46	.39	.54	.45	.39	.51	.44	.38	.49	.43	.38	.47	.41	.37	.35
7.0	.50	.41	.35	.49	.40	.34	.47	.39	.34	.45	.38	.33	.43	.37	.33	.31
8.0	.45	.37	.31	.44	.36	.31	.43	.35	.30	.41	.34	.30	.40	.34	.29	.27
9.0	.42	.33	.28	.41	.33	.28	.39	.32	.27	.38	.31	.27	.36	.31	.26	.24
10.0	.38	.30	.25	.38	.30	.25	.36	.29	.25	.35	.29	.24	.34	.28	.24	.22



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.322	.183	.058	.313	.179	.057	.297	.171	.054	.282	.163	.052	.269	.156	.050	
2.0	.298	.163	.050	.290	.160	.049	.276	.153	.048	.262	.147	.046	.250	.141	.045	
3.0	.273	.146	.044	.267	.143	.043	.254	.137	.042	.242	.132	.041	.231	.128	.040	
4.0	.251	.131	.038	.245	.128	.038	.234	.124	.037	.223	.120	.036	.213	.116	.035	
5.0	.232	.118	.034	.226	.116	.034	.216	.112	.033	.206	.109	.032	.197	.105	.032	
6.0	.214	.107	.031	.209	.106	.030	.200	.103	.030	.191	.099	.029	.183	.096	.029	
7.0	.199	.098	.028	.195	.097	.028	.186	.094	.027	.178	.091	.027	.171	.089	.026	
8.0	.186	.091	.026	.182	.090	.025	.174	.087	.025	.167	.085	.024	.160	.082	.024	
9.0	.174	.084	.023	.170	.083	.023	.163	.081	.023	.157	.079	.023	.151	.077	.022	
10.0	.163	.078	.022	.160	.077	.022	.154	.075	.021	.148	.073	.021	.142	.072	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.230	.230	.230	.196	.196	.196	.134	.134	.134	.077	.077	.077	.025	.025	.025	
1.0	.221	.195	.173	.189	.168	.149	.129	.115	.103	.074	.067	.060	.024	.021	.019	
2.0	.213	.172	.137	.182	.148	.118	.125	.102	.083	.072	.059	.048	.023	.019	.016	
3.0	.205	.154	.114	.176	.133	.099	.121	.092	.069	.070	.054	.041	.022	.018	.013	
4.0	.197	.141	.098	.169	.122	.085	.117	.085	.060	.067	.050	.036	.022	.016	.012	
5.0	.190	.131	.087	.163	.113	.076	.112	.079	.054	.065	.046	.032	.021	.015	.010	
6.0	.183	.123	.079	.157	.106	.069	.108	.074	.049	.063	.044	.029	.020	.014	.010	
7.0	.176	.116	.074	.151	.100	.064	.105	.070	.045	.061	.041	.027	.020	.014	.009	
8.0	.170	.110	.069	.146	.095	.060	.101	.067	.043	.059	.040	.026	.019	.013	.008	
9.0	.163	.105	.066	.141	.091	.057	.098	.064	.041	.057	.038	.024	.018	.012	.008	
10.0	.158	.101	.063	.136	.088	.055	.094	.062	.039	.055	.036	.023	.018	.012	.008	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm											
NAME: NMS1217-Plus					TYPE:			WEIGHT:			
SPEC.:NMS1217-9GW24CSN050CSXXX-Plus					DIM.: 1000*12*17mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*12			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	24.2	25.7	24.6	26.0	26.3	23.7	25.2	24.1	25.5	25.8	
	3H	25.9	27.3	26.3	27.6	28.0	25.2	26.6	25.6	26.9	27.2
	4H	26.7	28.0	27.1	28.3	28.7	25.8	27.1	26.2	27.4	27.8
	6H	27.3	28.5	27.7	28.9	29.3	26.2	27.4	26.6	27.7	28.1
	8H	27.6	28.8	28.0	29.1	29.5	26.3	27.4	26.7	27.8	28.2
	12H	27.9	29.0	28.3	29.4	29.8	26.3	27.4	26.7	27.8	28.2
4H	2H	24.8	26.1	25.2	26.5	26.8	24.5	25.8	24.9	26.1	26.5
	3H	26.7	27.9	27.2	28.2	28.7	26.1	27.3	26.6	27.7	28.1
	4H	27.6	28.6	28.1	29.1	29.5	26.8	27.9	27.3	28.3	28.7
	6H	28.4	29.3	28.9	29.8	30.2	27.4	28.3	27.8	28.7	29.2
	8H	28.8	29.6	29.3	30.1	30.6	27.5	28.4	28.0	28.8	29.3
	12H	29.1	29.9	29.6	30.4	30.9	27.6	28.4	28.1	28.9	29.4
8H	4H	27.9	28.8	28.4	29.2	29.7	27.2	28.1	27.7	28.5	29.0
	6H	28.9	29.6	29.4	30.1	30.6	27.9	28.7	28.5	29.1	29.7
	8H	29.4	30.0	29.9	30.5	31.1	28.2	28.8	28.8	29.4	29.9
	12H	29.9	30.4	30.4	30.9	31.5	28.4	28.9	29.0	29.5	30.1
12H	4H	27.9	28.7	28.4	29.2	29.7	27.3	28.1	27.8	28.5	29.1
	6H	29.0	29.6	29.5	30.1	30.7	28.1	28.7	28.6	29.2	29.8
	8H	29.5	30.0	30.1	30.6	31.2	28.4	28.9	29.0	29.5	30.1
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2				+ 0.2 / - 0.2						
1.5H	+ 0.2 / - 0.3				+ 0.2 / - 0.4						
2.0H	+ 0.1 / - 0.3				+ 0.2 / - 0.4						

CIE Pub.117, 208.7 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -5.4)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	55	43	36	54	43	36	53	43	36	30
0.80	65	53	46	64	53	45	62	52	45	38
1.00	73	62	54	72	61	54	69	62	53	46
1.25	80	69	62	79	69	62	76	67	60	53
1.50	85	75	68	83	74	67	80	72	66	57
2.00	92	83	76	90	82	76	86	79	74	65
2.50	96	88	82	94	86	81	89	83	78	69
3.00	100	92	87	97	91	85	92	87	83	73
4.00	104	98	93	101	96	91	96	92	88	77
5.00	107	101	97	104	99	95	98	95	91	80
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2021-03-01

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

AAI Figure

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Flux out:140.1 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2021-03-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	5219
L_0~180(75)av	5037
L_0~180(85)av	6512
L_90~270(65)av	4568
L_90~270(75)av	3928
L_90~270(85)av	2937
L_45(65)av	4988
L_45(75)av	4658
L_45(85)av	5325

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-01

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.4285A P:10.28W PF:1.000 Freq:0Hz Lamp Flux:208.747x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-9GW24CSN050CSXXXX-Plus	DIM.: 1000*12*17mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	67.2	67.0	66.7	66.7	67.2	67.0	66.7	66.7										
5	67.2	66.9	66.5	66.3	66.8	66.5	66.3	66.5										
10	66.7	66.3	65.6	65.3	65.8	65.4	65.3	65.8										
15	65.7	65.3	64.1	63.8	64.3	63.7	63.7	64.5										
20	64.2	63.6	61.9	61.7	62.2	61.5	61.5	62.7										
25	61.9	61.4	59.3	58.9	59.6	58.8	58.8	60.3										
30	59.2	58.6	56.1	55.6	56.6	55.7	55.4	57.5										
35	56.0	55.3	52.5	52.1	53.1	52.2	51.8	54.1										
40	52.3	51.5	48.4	48.3	49.2	48.2	47.7	50.2										
45	48.1	47.3	44.0	44.0	44.9	43.9	43.3	46.0										
50	43.5	42.7	39.3	39.4	40.4	39.2	38.5	41.3										
55	38.5	37.8	34.2	34.6	35.6	34.3	33.5	36.4										
60	33.2	32.6	28.9	29.5	30.5	29.2	28.3	31.2										
65	27.7	27.1	23.4	24.2	25.2	24.0	23.0	25.8										
70	22.2	21.6	17.8	18.8	19.8	18.6	17.5	20.4										
75	16.7	16.0	12.2	13.4	14.6	13.4	12.2	15.0										
80	11.5	10.8	7.01	8.52	9.86	8.74	7.27	10.0										
85	7.37	6.40	2.81	4.83	6.25	5.13	3.34	5.91										
90	4.86	3.72	0.51	3.07	4.42	3.54	0.92	3.54										
95	4.18	3.01	0.39	2.64	3.84	3.08	0.48	2.97										
100	4.00	2.85	0.22	2.41	3.63	2.88	0.15	2.47										
105	3.88	2.70	0.23	2.24	3.43	2.69	0.22	2.58										
110	3.73	2.44	0.27	2.04	3.31	2.47	0.29	2.29										
115	3.59	2.08	0.33	1.83	3.09	2.00	0.37	1.76										
120	3.34	1.56	0.41	1.62	2.85	1.79	0.43	1.48										
125	2.78	1.38	0.49	1.59	2.55	1.66	0.49	1.27										
130	2.33	1.30	0.53	1.35	2.33	1.52	0.55	1.16										
135	2.07	1.20	0.61	1.07	2.06	1.21	0.59	1.06										
140	1.84	0.86	0.65	0.77	1.78	0.77	0.63	0.79										
145	1.66	0.76	0.71	0.82	1.30	0.80	0.67	0.72										
150	1.07	0.77	0.73	0.88	0.84	0.83	0.73	0.69										
155	0.99	0.79	0.77	0.94	0.85	0.85	0.81	0.71										
160	0.98	0.83	0.85	0.98	0.86	0.95	0.89	0.73										
165	0.98	0.88	0.95	1.00	0.86	0.96	0.97	0.82										
170	0.97	0.97	1.02	1.06	0.86	0.99	1.04	0.94										
175	0.96	1.06	1.06	1.11	0.87	1.05	1.12	1.05										
180	0.96	1.12	1.16	1.16	0.96	1.12	1.17	1.16										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: