


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 34.17 lm/W			
MODEL	NMT1312-Plus	I _{max} (cd)	105.7	S/MH(C0/180)	1.28
NOMINAL POWER(W)	9.6	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	334.15	h UP,DN(C0-180)	2.9,47.3
NOMINAL FLUX(lm)	334.146	CIE CLASS	DIRECT	h UP,DN(C180-360)	2.8,47.0
LAMPS INSIDE	1	h up(%)	5.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	94.3	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	104.2	104.0	103.2	103.8	104.9	103.9	102.7	103.0	0- 10	9.976	9.976	2.99,2.99
20	99.32	99.04	97.48	99.13	100.7	98.86	96.49	97.61	10- 20	28.68	38.65	11.6,11.6
30	91.09	90.65	88.12	90.86	92.87	90.25	86.97	88.84	20- 30	43.63	82.29	24.6,24.6
40	79.86	79.24	75.86	79.54	81.93	78.81	74.61	77.29	30- 40	52.86	135.2	40.4,40.4
50	66.20	65.28	61.30	65.60	68.27	64.83	60.14	63.36	40- 50	55.27	190.4	57,57
60	50.54	49.52	45.03	49.84	52.61	48.99	44.04	47.68	50- 60	50.63	241.0	72.1,72.1
70	33.58	32.44	27.66	32.77	35.62	32.00	26.95	30.89	60- 70	39.65	280.7	84,84
80	17.40	15.86	10.93	16.10	19.04	15.72	10.62	14.89	70- 80	24.35	305.1	91.3,91.3
90	8.078	5.897	0.7911	5.852	8.548	6.010	0.7121	5.479	80- 90	9.959	315.0	94.3,94.3
100	7.188	4.986	0.3473	4.708	7.199	5.097	0.2004	4.287	90-100	5.008	320.0	95.8,95.8
110	6.527	4.267	0.4206	4.053	6.463	4.457	0.4208	3.814	100-110	4.261	324.3	97,97
120	5.745	3.419	0.7143	3.197	5.575	3.761	0.6145	3.047	110-120	3.506	327.8	98.1,98.1
130	4.698	2.757	0.9550	1.683	4.460	1.999	0.7819	2.465	120-130	2.643	330.4	98.9,98.9
140	3.515	1.767	1.102	1.149	2.204	1.122	0.9221	1.110	130-140	1.634	332.1	99.4,99.4
150	1.635	1.329	1.222	1.316	1.276	1.256	1.096	1.035	140-150	0.8968	333.0	99.6,99.6
160	1.583	1.396	1.369	1.490	1.416	1.449	1.363	1.169	150-160	0.6126	333.6	99.8,99.8
170	1.630	1.530	1.603	1.650	1.449	1.596	1.630	1.490	160-170	0.4202	334.0	100,100
180	1.576	1.810	1.790	1.803	1.543	1.797	1.810	1.810	170-180	0.1551	334.1	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	9905	3714
80	7707	4844
75	7479	5653
70	7552	6220
65	7670	6629
60	7776	6928
55	7860	7155
50	7923	7336
45	7979	7490


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.18	1.18	1.18	1.14	1.14	1.14	1.08	1.08	1.08	1.02	1.02	1.02	.97	.97	.97	.94
1.0	1.02	.97	.93	.99	.95	.91	.94	.90	.87	.89	.86	.84	.84	.82	.80	.78
2.0	.88	.81	.75	.86	.79	.74	.81	.76	.71	.77	.73	.69	.73	.70	.67	.64
3.0	.77	.69	.62	.75	.68	.61	.71	.65	.60	.68	.62	.58	.65	.60	.56	.54
4.0	.68	.59	.53	.67	.58	.52	.63	.56	.51	.60	.54	.49	.58	.52	.48	.46
5.0	.61	.52	.45	.59	.51	.45	.57	.49	.44	.54	.48	.43	.52	.46	.42	.39
6.0	.55	.46	.39	.54	.45	.39	.51	.44	.38	.49	.42	.37	.47	.41	.36	.34
7.0	.50	.41	.35	.48	.40	.34	.46	.39	.34	.44	.38	.33	.43	.37	.32	.30
8.0	.45	.37	.31	.44	.36	.30	.42	.35	.30	.41	.34	.29	.39	.33	.29	.27
9.0	.41	.33	.28	.41	.33	.27	.39	.32	.27	.38	.31	.26	.36	.30	.26	.24
10.0	.38	.30	.25	.37	.30	.25	.36	.29	.24	.35	.28	.24	.34	.28	.24	.22



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.324	.184	.058	.315	.180	.057	.298	.171	.055	.283	.163	.052	.269	.156	.050	
2.0	.299	.164	.050	.291	.160	.049	.276	.154	.048	.263	.147	.046	.250	.141	.045	
3.0	.274	.146	.044	.267	.143	.043	.254	.138	.042	.242	.132	.041	.230	.128	.039	
4.0	.252	.131	.038	.245	.128	.038	.234	.124	.037	.223	.120	.036	.212	.115	.035	
5.0	.232	.118	.034	.226	.116	.034	.216	.112	.033	.206	.109	.032	.197	.105	.032	
6.0	.215	.108	.031	.210	.106	.030	.200	.102	.030	.191	.099	.029	.183	.096	.029	
7.0	.199	.099	.028	.195	.097	.028	.186	.094	.027	.178	.091	.027	.170	.089	.026	
8.0	.186	.091	.026	.182	.090	.025	.174	.087	.025	.167	.084	.024	.160	.082	.024	
9.0	.174	.084	.024	.170	.083	.023	.163	.081	.023	.156	.078	.022	.150	.076	.022	
10.0	.163	.078	.022	.160	.077	.022	.154	.075	.021	.147	.073	.021	.142	.071	.020	

rcc	80%			70%			50%			30%			10%			0	
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
rfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.234	.234	.234	.200	.200	.200	.137	.137	.137	.078	.078	.078	.025	.025	.025		
1.0	.225	.200	.177	.193	.172	.153	.132	.118	.106	.076	.068	.061	.024	.022	.020		
2.0	.217	.176	.141	.186	.152	.122	.128	.105	.085	.074	.061	.050	.024	.020	.016		
3.0	.210	.159	.118	.180	.137	.103	.123	.095	.072	.071	.056	.042	.023	.018	.014		
4.0	.202	.146	.103	.173	.126	.089	.119	.088	.063	.069	.051	.037	.022	.017	.012		
5.0	.195	.136	.092	.167	.117	.080	.115	.082	.056	.067	.048	.033	.022	.016	.011		
6.0	.188	.127	.084	.161	.110	.073	.111	.077	.052	.065	.045	.031	.021	.015	.010		
7.0	.181	.120	.078	.155	.104	.068	.107	.073	.048	.062	.043	.029	.020	.014	.010		
8.0	.174	.115	.074	.150	.100	.064	.104	.070	.046	.060	.041	.027	.020	.014	.009		
9.0	.168	.110	.070	.145	.095	.061	.100	.067	.044	.058	.040	.026	.019	.013	.009		
10.0	.162	.106	.068	.140	.092	.059	.097	.065	.042	.057	.038	.025	.018	.013	.008		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm											
NAME: NMT1312-Plus					TYPE:			WEIGHT:			
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus					DIM.: 1000*13*12mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*13			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	23.6	25.1	23.9	25.4	25.7	23.2	24.7	23.5	25.0	25.3	
	3H	25.3	26.6	25.7	27.0	27.3	24.7	26.0	25.1	26.4	26.7
	4H	26.0	27.3	26.4	27.6	28.0	25.2	26.5	25.6	26.9	27.2
	6H	26.6	27.8	27.1	28.2	28.6	25.6	26.8	26.0	27.2	27.6
	8H	26.9	28.1	27.3	28.5	28.9	25.7	26.9	26.1	27.3	27.7
	12H	27.2	28.3	27.6	28.7	29.1	25.8	26.9	26.2	27.3	27.7
4H	2H	24.2	25.5	24.6	25.8	26.2	23.9	25.2	24.3	25.5	25.9
	3H	26.1	27.2	26.5	27.6	28.0	25.6	26.7	26.0	27.1	27.5
	4H	26.9	28.0	27.4	28.4	28.8	26.3	27.3	26.7	27.7	28.2
	6H	27.7	28.6	28.2	29.1	29.6	26.8	27.7	27.3	28.1	28.6
	8H	28.1	28.9	28.6	29.4	29.9	26.9	27.8	27.4	28.2	28.8
	12H	28.4	29.2	28.9	29.7	30.2	27.0	27.8	27.5	28.3	28.8
8H	4H	27.2	28.1	27.7	28.5	29.0	26.6	27.5	27.1	27.9	28.4
	6H	28.2	28.9	28.7	29.4	29.9	27.3	28.0	27.9	28.5	29.1
	8H	28.6	29.3	29.2	29.8	30.4	27.6	28.2	28.1	28.7	29.3
	12H	29.1	29.7	29.7	30.2	30.8	27.8	28.3	28.3	28.9	29.5
12H	4H	27.2	28.0	27.7	28.5	29.0	26.7	27.4	27.2	27.9	28.5
	6H	28.2	28.9	28.8	29.4	30.0	27.4	28.1	28.0	28.6	29.2
	8H	28.8	29.3	29.3	29.9	30.5	27.8	28.3	28.3	28.8	29.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.4					

CIE Pub.117, 334.1 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.8)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	55	43	36	54	43	36	53	42	36	29
0.80	65	53	45	64	52	45	61	51	44	37
1.00	73	61	54	72	61	54	69	62	53	45
1.25	80	69	62	78	68	61	75	66	60	52
1.50	85	75	67	83	74	67	79	71	65	57
2.00	92	83	76	90	81	75	86	79	73	64
2.50	96	88	81	94	86	80	89	83	78	68
3.00	100	92	86	97	90	85	92	87	82	72
4.00	104	98	92	101	95	91	96	91	87	77
5.00	106	101	97	103	99	95	98	94	91	80
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

Flux out:231.6 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	7860
L_0~180(75)av	7764
L_0~180(85)av	10425
L_90~270(65)av	6548
L_90~270(75)av	5577
L_90~270(85)av	3746
L_45(65)av	7390
L_45(75)av	6998
L_45(85)av	8149

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-01

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.4075A P:9.779W PF:1.000 Freq:0Hz Lamp Flux:334.146x1 lm		
NAME: NMT1312-Plus	TYPE:	WEIGHT:
SPEC.:NMT1312-9GW24CSN050CSXXX-Plus	DIM.: 1000*13*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	106	105	105	105	106	105	105	105										
5	105	105	105	105	106	105	104	104										
10	104	104	103	104	105	104	103	103										
15	102	102	101	102	103	102	100	101										
20	99.3	99.0	97.5	99.1	101	98.9	96.5	97.6										
25	95.6	95.3	93.2	95.4	97.2	95.0	92.1	93.6										
30	91.1	90.6	88.1	90.9	92.9	90.3	87.0	88.8										
35	85.8	85.3	82.3	85.6	87.8	84.9	81.1	83.4										
40	79.9	79.2	75.9	79.5	81.9	78.8	74.6	77.3										
45	73.3	72.6	68.9	72.9	75.4	72.1	67.6	70.6										
50	66.2	65.3	61.3	65.6	68.3	64.8	60.1	63.4										
55	58.6	57.6	53.4	57.9	60.6	57.1	52.3	55.7										
60	50.5	49.5	45.0	49.8	52.6	49.0	44.0	47.7										
65	42.1	41.1	36.4	41.4	44.2	40.6	35.5	39.3										
70	33.6	32.4	27.7	32.8	35.6	32.0	26.9	30.9										
75	25.2	23.9	19.0	24.2	27.1	23.5	18.5	22.6										
80	17.4	15.9	10.9	16.1	19.0	15.7	10.6	14.9										
85	11.2	9.39	4.21	9.51	12.4	9.36	4.28	8.66										
90	8.08	5.90	0.79	5.85	8.55	6.01	0.71	5.48										
95	7.50	5.27	0.61	5.04	7.55	5.40	0.13	4.96										
100	7.19	4.99	0.35	4.71	7.20	5.10	0.20	4.29										
105	6.87	4.59	0.34	4.38	6.83	4.81	0.30	4.27										
110	6.53	4.27	0.42	4.05	6.46	4.46	0.42	3.81										
115	6.16	3.66	0.60	3.38	6.06	4.10	0.52	3.53										
120	5.74	3.42	0.71	3.20	5.58	3.76	0.61	3.05										
125	5.07	3.27	0.83	2.87	4.96	3.42	0.71	2.80										
130	4.70	2.76	0.95	1.68	4.46	2.00	0.78	2.47										
135	4.16	2.33	1.03	1.23	3.94	1.51	0.86	2.04										
140	3.51	1.77	1.10	1.15	2.20	1.12	0.92	1.11										
145	2.89	1.31	1.15	1.23	1.68	1.17	1.00	1.01										
150	1.64	1.33	1.22	1.32	1.28	1.26	1.10	1.03										
155	1.54	1.36	1.26	1.42	1.34	1.38	1.22	1.06										
160	1.58	1.40	1.37	1.49	1.42	1.45	1.36	1.17										
165	1.62	1.44	1.50	1.56	1.45	1.48	1.49	1.29										
170	1.63	1.53	1.60	1.65	1.45	1.60	1.63	1.49										
175	1.55	1.67	1.71	1.74	1.46	1.68	1.75	1.62										
180	1.58	1.81	1.79	1.80	1.54	1.80	1.81	1.81										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: