


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 39.91 lm/W			
MODEL	NMS1217	I <sub>max</sub> (cd)	119.6	S/MH(C0/180)	1.33
NOMINAL POWER(W)	10.1	LOR(%)	100.0	S/MH(C90/270)	1.26
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	403.05	h UP,DN(C0-180)	3.3,45.5
NOMINAL FLUX(lm)	403.054	CIE CLASS	DIRECT	h UP,DN(C180-360)	3.7,47.4
LAMPS INSIDE	1	h up(%)	7.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	93.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:COLORS  
 Test Date:2019-05-16

g Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.750m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C90	C180	C270					g	F zone	F total	%lum,lamp
10	117.7	117.2	118.8	117.4					0~ 10	11.33	11.33	2.81,2.81
20	112.5	110.9	114.9	111.3					10~ 20	32.63	43.96	10.9,10.9
30	103.8	100.9	107.3	101.5					20~ 30	49.93	93.88	23.3,23.3
40	91.98	87.61	96.13	88.53					30~ 40	61.05	154.9	38.4,38.4
50	77.45	71.86	82.06	72.95					40~ 50	64.71	219.6	54.5,54.5
60	60.64	53.97	65.18	55.24					50~ 60	60.49	280.1	69.5,69.5
70	42.25	34.50	46.29	35.95					60~ 70	48.87	329.0	81.6,81.6
80	23.92	14.54	27.02	16.48					70~ 80	31.66	360.7	89.5,89.5
90	11.86	0.7919	13.39	2.774					80~ 90	14.00	374.7	93.93
100	9.122	0.4961	10.29	0.4891					90~100	6.207	380.9	94.5,94.5
110	8.898	0.8435	9.842	0.8750					100~110	5.420	386.3	95.8,95.8
120	8.054	1.146	9.193	1.171					110~120	4.967	391.3	97.1,97.1
130	7.120	1.410	8.143	1.396					120~130	4.220	395.5	98.1,98.1
140	5.839	1.622	6.515	1.526					130~140	3.261	398.7	98.9,98.9
150	3.606	1.809	5.002	1.790					140~150	2.214	400.9	99.5,99.5
160	2.363	2.125	2.768	2.041					150~160	1.216	402.2	99.8,99.8
170	2.266	2.479	2.323	2.388					160~170	0.6642	402.8	99.9,99.9
180	2.273	2.685	2.273	2.665					170~180	0.2274	403.1	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-05-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.750m [K=1.0000]  
Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	15778	5569
80	11479	6976
75	10565	7872
70	10295	8406
65	10175	8754
60	10106	8996
55	10069	9177
50	10040	9316
45	10020	9429


C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-05-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.750m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.17	1.17	1.17	1.14	1.14	1.14	1.07	1.07	1.07	1.01	1.01	1.01	.96	.96	.96	.93
1.0	1.01	.96	.92	.98	.94	.90	.92	.89	.86	.87	.85	.82	.83	.80	.78	.76
2.0	.87	.80	.74	.85	.78	.73	.80	.75	.70	.76	.71	.67	.72	.68	.65	.62
3.0	.76	.68	.61	.74	.66	.60	.70	.64	.58	.66	.61	.56	.63	.58	.54	.52
4.0	.67	.58	.51	.66	.57	.51	.62	.55	.49	.59	.53	.48	.56	.51	.46	.44
5.0	.60	.51	.44	.58	.50	.43	.55	.48	.42	.53	.46	.41	.50	.45	.40	.38
6.0	.54	.45	.38	.52	.44	.38	.50	.42	.37	.48	.41	.36	.45	.40	.35	.33
7.0	.49	.40	.34	.48	.39	.33	.45	.38	.32	.43	.37	.32	.41	.35	.31	.29
8.0	.44	.36	.30	.43	.35	.29	.41	.34	.29	.40	.33	.28	.38	.32	.28	.26
9.0	.41	.32	.27	.40	.32	.26	.38	.31	.26	.36	.30	.25	.35	.29	.25	.23
10.0	.37	.29	.24	.37	.29	.24	.35	.28	.23	.34	.27	.23	.32	.27	.23	.21



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-05-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.750m [K=1.0000]  
Remarks:

## WEC AND CCEC

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.333	.190	.060	.324	.185	.059	.307	.176	.056	.291	.168	.054	.276	.160	.052	
2.0	.305	.167	.051	.297	.164	.050	.281	.156	.049	.267	.150	.047	.254	.144	.045	
3.0	.279	.148	.044	.271	.145	.044	.257	.139	.042	.245	.134	.041	.233	.129	.040	
4.0	.255	.133	.039	.248	.130	.038	.236	.125	.037	.224	.120	.036	.214	.116	.035	
5.0	.234	.119	.035	.229	.117	.034	.217	.113	.033	.207	.109	.032	.197	.105	.032	
6.0	.217	.109	.031	.211	.107	.031	.201	.103	.030	.192	.100	.029	.183	.096	.029	
7.0	.201	.099	.028	.196	.098	.028	.187	.095	.027	.178	.091	.027	.170	.088	.026	
8.0	.187	.091	.026	.183	.090	.025	.175	.087	.025	.167	.084	.024	.159	.082	.024	
9.0	.175	.085	.024	.171	.083	.023	.164	.081	.023	.156	.078	.022	.150	.076	.022	
10.0	.164	.079	.022	.161	.078	.022	.154	.075	.021	.147	.073	.021	.141	.071	.020	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.244	.244	.244	.209	.209	.209	.142	.142	.142	.082	.082	.082	.026	.026	.026	
1.0	.236	.210	.187	.202	.180	.161	.138	.124	.111	.080	.072	.065	.025	.023	.021	
2.0	.229	.186	.151	.196	.160	.130	.134	.111	.091	.077	.065	.053	.025	.021	.017	
3.0	.221	.169	.128	.189	.146	.111	.130	.101	.078	.075	.059	.046	.024	.019	.015	
4.0	.213	.156	.112	.183	.135	.098	.126	.094	.069	.073	.055	.041	.023	.018	.013	
5.0	.206	.146	.102	.177	.126	.089	.122	.088	.063	.071	.052	.037	.023	.017	.012	
6.0	.199	.138	.094	.171	.119	.082	.118	.084	.058	.068	.049	.034	.022	.016	.011	
7.0	.192	.131	.088	.165	.114	.077	.114	.080	.055	.066	.047	.033	.021	.015	.011	
8.0	.185	.125	.084	.159	.109	.073	.110	.076	.052	.064	.045	.031	.021	.015	.010	
9.0	.179	.120	.081	.154	.104	.070	.107	.073	.050	.062	.043	.030	.020	.014	.010	
10.0	.173	.116	.078	.149	.101	.068	.104	.071	.048	.060	.042	.029	.020	.014	.010	

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-05-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.750m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm											
NAME: NMS1217-Plus					TYPE:			WEIGHT:1000*12*17			
SPEC.:NMS1217-9NW24NSN50MS0100-Plus					DIM.:			SERIAL No.:			
MFR.: Colors					SUR.:1000*12			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	23.7	25.1	24.0	25.4	25.8	23.2	24.7	23.6	25.0	25.4	
	3H	25.5	26.8	25.9	27.2	27.6	24.8	26.2	25.2	26.5	26.9
	4H	26.3	27.6	26.7	28.0	28.4	25.5	26.7	25.9	27.1	27.5
	6H	27.1	28.3	27.5	28.7	29.1	25.9	27.1	26.3	27.5	27.9
	8H	27.4	28.6	27.9	29.0	29.4	26.0	27.2	26.5	27.6	28.1
	12H	27.8	28.9	28.2	29.3	29.8	26.1	27.2	26.6	27.6	28.1
4H	2H	24.2	25.5	24.7	25.9	26.3	23.9	25.2	24.4	25.6	26.0
	3H	26.3	27.4	26.7	27.8	28.2	25.7	26.8	26.2	27.3	27.7
	4H	27.2	28.2	27.7	28.7	29.2	26.5	27.5	27.0	28.0	28.4
	6H	28.1	29.0	28.6	29.5	30.0	27.1	28.0	27.6	28.5	29.0
	8H	28.6	29.4	29.1	29.9	30.4	27.3	28.1	27.8	28.6	29.1
	12H	29.0	29.8	29.6	30.3	30.9	27.4	28.2	27.9	28.7	29.2
8H	4H	27.5	28.3	28.0	28.8	29.4	26.8	27.7	27.4	28.2	28.7
	6H	28.6	29.3	29.1	29.8	30.4	27.6	28.3	28.2	28.9	29.4
	8H	29.2	29.8	29.7	30.3	30.9	27.9	28.5	28.5	29.1	29.7
	12H	29.8	30.3	30.4	30.9	31.5	28.1	28.7	28.7	29.2	29.9
12H	4H	27.5	28.3	28.0	28.8	29.4	26.9	27.7	27.4	28.2	28.7
	6H	28.7	29.3	29.2	29.8	30.4	27.7	28.4	28.3	28.9	29.5
	8H	29.3	29.8	29.9	30.4	31.0	28.1	28.6	28.7	29.2	29.8
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3					+ 0.1 / - 0.4					

CIE Pub.117, 403.1 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.2)

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-05-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.750m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	54	42	35	53	42	35	51	41	34	28
0.80	64	51	44	62	51	44	60	50	43	36
1.00	72	60	52	70	59	52	67	60	51	43
1.25	79	68	60	77	67	59	74	65	58	50
1.50	84	73	66	82	72	65	78	70	63	55
2.00	91	82	75	89	80	73	84	77	71	62
2.50	95	87	80	93	85	79	88	81	76	66
3.00	99	91	85	96	89	83	91	85	80	70
4.00	103	96	91	100	94	89	94	90	86	75
5.00	106	100	95	102	98	93	97	93	89	78
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-05-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.750m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-05-16


deg Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.750m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:

Flux out:268.7 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-05-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.750m [K=1.0000]  
Remarks:

## ISOLUX DIAGRAM

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: COLORS  
Test Date: 2019-05-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.750m [K=1.0000]  
Remarks:

## LED Avg.L Report

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	10599
L_0~180(75)av	11157
L_0~180(85)av	16896
L_90~270(65)av	8883
L_90~270(75)av	8124
L_90~270(85)av	6638
L_45(65)av	9553
L_45(75)av	9299
L_45(85)av	10555

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:COLORS  
 Test Date:2019-05-16

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.750m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: COLORS  
Test Date: 2019-05-16

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.750m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.4220A P:10.10W PF:1.000 Freq:0Hz Lamp Flux:403.054x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:1000*12*17
SPEC.:NMS1217-9NW24NSN50MS0100-Plus	DIM.:	SERIAL No.:
MFR.: Colors	SUR.:1000*12	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	90	180	270															
0	120	119	120	119															
5	119	119	119	119															
10	118	117	119	117															
15	116	115	117	115															
20	112	111	115	111															
25	109	106	112	107															
30	104	101	107	101															
35	98.2	94.6	102	95.3															
40	92.0	87.6	96.1	88.5															
45	85.0	80.0	89.4	81.0															
50	77.4	71.9	82.1	73.0															
55	69.3	63.2	73.9	64.3															
60	60.6	54.0	65.2	55.2															
65	51.6	44.4	55.9	45.7															
70	42.3	34.5	46.3	35.9															
75	32.8	24.4	36.5	26.0															
80	23.9	14.5	27.0	16.5															
85	16.5	5.82	18.8	8.06															
90	11.9	0.79	13.4	2.77															
95	10.0	0.37	11.0	0.46															
100	9.12	0.50	10.3	0.49															
105	9.13	0.68	10.1	0.66															
110	8.90	0.84	9.84	0.88															
115	8.47	1.00	9.55	1.01															
120	8.05	1.15	9.19	1.17															
125	7.49	1.29	8.72	1.25															
130	7.12	1.41	8.14	1.40															
135	6.39	1.53	7.41	1.44															
140	5.84	1.62	6.51	1.53															
145	5.11	1.73	5.59	1.63															
150	3.61	1.81	5.00	1.79															
155	2.43	1.95	4.07	1.91															
160	2.36	2.12	2.77	2.04															
165	2.36	2.32	2.47	2.24															
170	2.27	2.48	2.32	2.39															
175	2.18	2.59	2.23	2.57															
180	2.27	2.68	2.27	2.67															

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2019-05-16

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.750m [K=1.0000]  
Remarks: