

# 120V Covalinear Tunable

## Linear LED Lightbar



Project Name	Type
Catalog #	Date

### PRODUCT OVERVIEW

An Energy Star compliant, fully encapsulated driverless 120V architectural LED linear lightbar that enables selection between three color temperatures. Covalinear is driverless and tunable, enabling 2700K, 3000K and 3500K light temperatures. Available in 9", 18", 24", 36" or 48" lengths. Frosted lens assures an even glow over the length of our fixture.



### FEATURES

- Tunable white 3CCT selectable switch (2700K, 3000K, 3500K)
- Up to 1230 lumens
- Dry location
- Diode free illumination
- Dimmable (Triac)
- 120° viewing angle
- Modular - units can be joined together for longer runs
- Maximum run on a given lead is 40'
- Operating temp. -4°F - 122°F\*



### SPECIFICATIONS

#### ELECTRICAL

- 120V
- 3.5W / 9 in
- 6.8W / 18 in
- 9W / 24 in
- 12.4W / 36 in
- 17W / 48 in

#### LABEL

- ETL
- Title 24 - JA8

#### OPTICS

- 2700K, 3000K, 3500K
- 90+ CRI

#### WARRANTY

- 5 years\*\*

\*\* Do not install in an application that is outside of the products listed ambient temperature and in an area that is not easily accessed for service requirements.

### Your Covalinear Specification Checklist:

1. Select Power Feed
2. Select Your Fixtures (bars)
3. Select Bar to Bar Connectors
4. Select Quick Box

### ORDERING INFORMATION

Example: CL24-TUN-WH

Model	Length (inches)	Color Temp.	Finish
CL	9	TUN (3CCT Selectable Switch 2700K, 3000K, 3500K)	WH (White)
	18		
	24		
	36		
	48		

# 120V Covalinear Tunable

## Linear LED Lightbar



### PRODUCT ORDERING

Catalog No.	Length	Color Temp.	Lumens	Wattage	CRI	Finish
CL9-TUN-WH	9" / 229mm	2700K	328	3.5W	90+	WHITE
		3000K	346			
		3500K	362			
CL18-TUN-WH	18" / 457mm	2700K	541	6.8W	90+	WHITE
		3000K	583			
		3500K	601			
CL24-TUN-WH	24" / 610mm	2700K	725	9W	90+	WHITE
		3000K	792			
		3500K	810			
CL36-TUN-WH	36" / 914mm	2700K	900	12.4W	90+	WHITE
		3000K	1007			
		3500K	961			
CL48-TUN-WH	48" / 1219mm	2700K	1337	17W	90+	WHITE
		3000K	1438			
		3500K	1476			

\* Based on 3000K. Each fixture comes with (2) standard mounting clips and (2) screws for surface mounting, (2) 45° mounting clips and (2) screws, and (1) CL1-BB-WH bar to bar connector.

### ACCESSORIES

Catalog No.	Description
CL1-BB-WH	Bar to Bar Direct Connector
CL6-BB-WH	6" Bar to Bar Connector
CL12-BB-WH	12" Bar to Bar Connector
CL24-BB-WH	24" Bar to Bar Connector
CL36-BB-WH	36" Bar to Bar Connector
CL6-PC-WH	Bar to 120V Power - 72" Cord and Plug
CL6-PCHW-WH	Bar to 120V POWER - 72" for Hardwire
CLQB-WH	Junction Box with Quick Connects - WHITE

# 120V Covalinear Tunable

## Linear LED Lightbar



### DIAGRAM

