

120V Covalinear Tunable

Linear LED Lightbar



PRODUCT OVERVIEW

An Energy Star compliant, fully encapsulated driverless 120V architectural LED linear lightbar that enables selection between three color temperatures. Covalinear is driverless and tunable, enabling 2700K, 3000K and 3500K light temperatures. Available in 9", 18", 24", 36" or 48" lengths. Frosted lens assures an even glow over the length of our fixture.

FEATURES

- Tunable white 3CCT selectable switch (2700K, 3000K, 3500K)
- Up to 1230 lumens
- Dry location
- Diode free illumination
- Dimmable (Triac)
- 120° viewing angle
- Modular - units can be joined together for longer runs
- Maximum run on a given lead is 40'
- Operating temp. -4°F - 122°F*

SPECIFICATIONS

ELECTRICAL

- 120V
- 3.5W / 9 in
- 6.8W / 18 in
- 9W / 24 in
- 12.4W / 36 in
- 17W / 48 in

LABEL

- ETL
- Title 24 - JA8
- Energy Star

OPTICS

- 2700K, 3000K, 3500K
- 90+ CRI

WARRANTY

- 5 years**

** Do not install in an application that is outside of the products listed ambient temperature and in an area that is not easily accessed for service requirements.

Project Name	Type
Catalog #	Date



Your Covalinear Specification Checklist:

1. Select Power Feed
2. Select Your Fixtures (bars)
3. Select Bar to Bar Connectors
4. Select Quick Box

ORDERING INFORMATION

Example: CL24-TUN-WH

Model	Length (inches)	Color Temp.	Finish
CL	9	TUN (3CCT Selectable Switch 2700K, 3000K, 3500K)	WH White
	18		
	24		
	36		
	48		

120V Covalinear Tunable

Linear LED Lightbar

PRODUCT ORDERING

Catalog No.	Length	Wattage	Lumens*	Color Temp.	CRI	Finish
CL9-TUN-WH	9" / 229mm	3.5W	280	3CCT Selectable Switch 2700K, 3000K, 3500K	90+	WHITE
CL18-TUN-WH	18" / 457mm	6.8W	530			
CL24-TUN-WH	24" / 610mm	9W	685			
CL36-TUN-WH	36" / 914mm	12.4W	930			
CL48-TUN-WH	48" / 1219mm	17W	1230			

* Based on 3000K. Each fixture comes with (2) standard mounting clips and (2) screws for surface mounting, (2) 45° mounting clips and (2) screws, and (1) CL1-BB-WH bar to bar connector.

ACCESSORIES

Catalog No.	Description
CL1-BB-WH	Bar to Bar Direct Connector
CL6-BB-WH	6" Bar to Bar Connector
CL12-BB-WH	12" Bar to Bar Connector
CL24-BB-WH	24" Bar to Bar Connector
CL36-BB-WH	36" Bar to Bar Connector
CL6-PC-WH	Bar to 120V Power - 72" Cord and Plug
CL6-PCHW-WH	Bar to 120V POWER - 72" for Hardwire
CLQB-WH	Junction Box with Quick Connects - WHITE

DIAGRAM

