LTR-P Professional Series

4.5W, 24VDC LED Tape Specification Sheet

GMLighting®

Project Name	Type
Catalog #	Date


24 VOLT | DRY LOCATION | CLASS 2 | TITLE 24 | LUX control | 90+ CRI | ETL Intertek | 5 Yr. WARRANTY

PRODUCT OVERVIEW

GM's Professional Series Flexible LED Tape combines style and technology with reliability. Designed for professional installations that demand a high level of quality, the LTR-P Series includes a wide array of key features and is available in 16'-4" (5M) and 100' (30M) reels.

FEATURES

- 24VDC models
- 2400K, 2700K, 3000K, 3500K, 4000K and 5000K color temps
- Remote control with GM's LUXcontrol™ App and controllers
- Dry location
- 120 LEDs per meter
- Cuttable every 2"
- Custom lengths available - consult factory
- Premium diodes
- 120° viewing angle
- Dimmable
- 3M adhesive back
- Maximum run on a given lead is 20'
- Includes Sure-Tite connectors



SPECIFICATIONS

ELECTRICAL

- 24V
- 4.5 watts per foot

OPTICS

- 90+ CRI

OPERATING TEMP

- -4°F to 122°F
- For proper thermal management, we recommend to mount this product in a channel

CERTIFICATION

- ETL
- Title 24 compliant when used with used with specific drivers. Consult factory.
- Class 2

WARRANTY

- 5-year warranty when paired with GM power supply

Note: Do not install in an application that is not easily accessed for service. Our warranty covers product only and does not cover any labor or incidental charges related to service or warranty.

ORDERING INFORMATION

Example: LTR-P-24V-4.5W-24K-16

Model	-	Series	-	Voltage	-	Wattage	-	Color Temp	-	Reel Length
LTR		P		24V		4.5W		24K		16
								27K		
								30K		
								35K		100
								40K		
								50K		

*Reel Length: 16 = 16'-4", 100 = 98'-6"

ACCESSORIES

Product No.	Description
ESTC-1	Sure-Tite tape to tape connector
ESTC-90	Sure-Tite 90° connector
ESTLK-60	Sure-Tite 60" adjustable tape to tape connector
ESTW-60	Sure-Tite 60" adjustable tape to power connector
ESTW-CO	Sure-Tite tape to power supply connector (no wire)

Your LED Tape Specification Checklist:

1. Select Tape
2. Select Connectors
3. Select Channels
4. Select Controllers or Dimmers
5. Select Power Supplies

Install Sheet

©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice
18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net

LTR-P Professional Series

4.5W, 24VDC LED Tape
Specification Sheet

GMLighting®

Product No.	Length	Lumens per ft.	CRI	Color Temp.	Max. Run
LTR-P-24V-4.5W-24K-16	16’-4” / 5M	299	90+	2400K	20’
LTR-P-24V-4.5W-27K-16	16’-4” / 5M	341	90+	2700K	20’
LTR-P-24V-4.5W-30K-16	16’-4” / 5M	342	90+	3000K	20’
LTR-P-24V-4.5W-35K-16	16’-4” / 5M	382	90+	3500K	20’
LTR-P-24V-4.5W-40K-16	16’-4” / 5M	389	90+	4000K	20’
LTR-P-24V-4.5W-50K-16	16’-4” / 5M	425	90+	5000K	20’
LTR-P-24V-4.5W-24K-100	98’-6” / 30M	299	90+	2400K	20’
LTR-P-24V-4.5W-27K-100	98’-6” / 30M	341	90+	2700K	20’
LTR-P-24V-4.5W-30K-100	98’-6”/ 30M	342	90+	3000K	20’
LTR-P-24V-4.5W-35K-100	98’-6” / 30M	382	90+	3500K	20’
LTR-P-24V-4.5W-40K-100	98’-6” / 30M	389	90+	4000K	20’
LTR-P-24V-4.5W-50K-100	98’-6”/ 30M	425	90+	5000K	20’

Kelvin temperature (color) ±100K.
16’-4” and 100’ reel includes 48” lead affixed to tape. 16’-4” reel includes (3) ESTW-60 Sure-Tite connectors. 100’ reel includes (10) ESTW-60 Sure-Tite connectors

COMPATIBLE CONTROLLERS

Product No.	Description
SHWC	LUXcontrol Smart 2.4 GHz WiFi Controller, Standard 24V Low Voltage
SHWD	LUXcontrol Smart 2.4 GHz WiFi Dimmer, Standard 24V Low Voltage
SWDD60W24V	SwitchLD All-in-One Dimmer and Driver, 60W, 24VDC
SWDD96W24V	SwitchLD All-in-One Dimmer and Driver, 96W, 24VDC
HC-RF-UNV-5CH	Universal 1-5 Channel RF Remote Control
CM-RF-UNV-5CH	Universal 1-5 Channel Control Module
RPT-UNV-5CH	Universal 1-5 Channel Repeater Amplifier


COMPATIBLE DRIVERS

Product No.	Description	Watts	Specification Sheet
LD-XD-UNV	LineDrive Electronic Multi-Dimmable Power Supply, 24VDC	20W, 40W, 60W, 96W, 180W, 200W, 300W	View Spec Sheet
LD-MD-UNV	LineDrive Magnetic Dimmable Power Supply, 24VDC	30W, 60W, 96W, 150W, 200W, 300W	View Spec Sheet
LD-EDM	LineDrive Electronic Dimmable MINI Power Supply, 24VDC	60W	View Spec Sheet
LTP	Cord and Plug Power Supply, 24VDC	25W, 48W, 60W, 90W	View Spec Sheet
PSD	Electronic Dimmable Power Supply, 24VDC	15W, 24W, 60W, 90W	View Spec Sheet


NOTE: Please see our website for updated power supply specifications and information.

©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice
18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net

DIMENSION



EST SERIES CONNECTORS



©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice

18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net


LTR-P Professional Series

4.5W, 24VDC LED Tape
Specification Sheet


GMLighting®

COMPATIBLE CHANNELS - FIT CONNECTORS ON PG. 1


EXTRA DEEP

Product No.	Description	Length	Dimensions
LED-CHL-XD	Extra deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4’	
LED-CHL-XD-6	Extra deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	6’	
LED-CHL-XD-AMC	(2) Adjustable mounting brackets for LED-CHL-XD	N/A	
LED-CHL-XD-EC	(2) End caps for LED-CHL-XD. One solid, one with hole.	N/A	
LED-CHL-XD-MC	(2) Mounting clips and screws for LED-CHL-XD	N/A	


EXTRA DEEP FLANGED

LED-CHL-XD-F	Extra deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	4’	
LED-CHL-XD-F-6	Extra deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	6’	
LED-CHL-XD-F-DC	(2) Drywall mounting brackets for LED-CHL-XD-F	N/A	
LED-CHL-XD-F-EC	(2) End caps for LED-CHL-XD-F. One solid, one with hole.	N/A	

MINI DEEP

LED-CHL-XD-MD	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4’	
LED-CHL-XD-MD-WH	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws. White.	4’	
LED-CHL-XD-MD-B	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws. Black.	4’	
LED-CHL-XD-MD-6	Mini deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	6’	
LED-CHL-XD-MD-6-WH	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws. White.	6’	
LED-CHL-XD-MD-6-B	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws. Black.	6’	
LED-CHL-XD-MD-AMC	(2) Adjustable mounting brackets for LED-CHL-XD-MD	N/A	
LED-CHL-XD-MD-EC	(2) End caps for LED-CHL-XD-MD. One solid, one with hole.	N/A	
LED-CHL-XD-MD-MC	(2) Mounting clips for LED-CHL-XD-MD	N/A	

MINI DEEP FLANGED

LED-CHL-XD-MD-F	Mini deep format flanged extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	4’	
LED-CHL-XD-MD-F-WH	Mini deep format flanged extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws. White.	4’	
LED-CHL-XD-MD-F-B	Mini deep format flanged extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws. Black.	4’	
LED-CHL-XD-MD-F-6	Mini deep format extruded flanged channel with flange. Includes snap-on frosted lens with mounting clips and screws.	6’	
LED-CHL-XD-MD-F-6-WH	Mini deep format extruded flanged channel with flange. Includes snap-on frosted lens with mounting clips and screws. White.	6’	
LED-CHL-XD-MD-F-6-B	Mini deep format extruded flanged channel with flange. Includes snap-on frosted lens with mounting clips and screws. Black.	6’	
LED-CHL-XD-MD-F-DC	(2) Drywall mounting brackets for LED-CHL-XD-MD-F	N/A	
LED-CHL-XD-MD-F-EC	(2) End caps for LED-CHL-XD-MD-F One solid, one with hole.	N/A	

©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice
18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net


LTR-P Professional Series

4.5W, 24VDC LED Tape
Specification Sheet


GMLighting®

COMPATIBLE CHANNELS- FIT CONNECTORS ON PG. 1


45° ANGLE MOUNT

Product No.	Description	Length	Dimensions
LED-CHL-45	Extruded angled (45°) channel. Includes snap-on frosted lens with mounting clips and screws.	4’	
LED-CHL-45-EC	(2) End caps for LED-CHL-45 - one solid, one with hole	N/A	
LED-CHL-45-MC	(2) Mounting clips and screws for LED-CHL-45	N/A	


45° LARGE ANGLE MOUNT

LED-CHL-45-1200	Extruded angled (45°) channel. Includes snap-on frosted lens with mounting clips and screws.	4’	
LED-CHL-45-1200-EC	(2) End caps for LED-CHL-45 - one solid, one with hole	N/A	
LED-CHL-45-1200-MC	(2) Additional mounting clips for LED-CHL-45-1200	N/A	


WIDE

LED-CHL-W	Wide format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4’	
LED-CHL-W-6	Wide format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	6’	
LED-CHL-W-AMC	(2) Adjustable mounting brackets for LED-CHL-W	N/A	
LED-CHL-W-EC	(2) End caps for LED-CHL-W - one solid, one with hole.	N/A	
LED-CHL-W-MC	(2) Additional mounting clips for LED-CHL-W	N/A	

MUD IN - STANDARD

LED-CHL-MI-ST6	Standard extruded aluminum mud-in channel. Includes snap-on frosted lens.	6’	
LED-CHL-MI-ST-EC	(2) End caps for LED-CHL-MI-ST6 one solid, one with hole.	N/A	

STANDARD STRAIGHT

LED-CHL2-4-CA	Silver channel, white lens (2) mounting clips, (2) screws	4’	
LED-CHL2-4-WH	White channel, white lens (2) mounting clips, (2) screws	4’	
LED-CHL2-4-BK	Black channel, white lens (2) mounting clips, (2) screws	4’	
LED-CHL2-6-CA	Silver channel, whilte lens, (4) mounting clips, (4) screws	6’	
LED-CHL2-6-WH	White channel, whilte lens, (4) mounting clips, (4) screws	6’	
LED-CHL2-6-BK	Black channel, whilte lens, (4) mounting clips, (4) screws	6’	
LED-CHL2 LENS-4-BK	Lens in black for LED-CHL2-4	4’	
LED-CHL2 LENS-6-BK	Lens in black for LED-CHL2-6	6’	
LED-CHL2-ECG	(2) End caps for LED-CHL2-CA: light gray, one solid, one with hole	N/A	
LED-CHL2-ECW	(2) End caps for LED-CHL2-WH: white, one solid, one with hole	N/A	
LED-CHL2-ECB	(2) End caps for LED-CHL2-BK: black, one solid, one with hole	N/A	
LED-CHL2-MC	(2) Mounting clips and (2) screws	N/A	
LED-CHL2-AMC	(2) Adjustable mounting clips and (2) screws	N/A	

©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice
18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net


LTR-P Professional Series

4.5W, 24VDC LED Tape
Specification Sheet


GMLighting®

COMPATIBLE CHANNELS - SOLDERED LEADS ONLY


STANDARD STRAIGHT

Product No.	Description	Length	Dimensions
LED-CHL	Extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4’	
LED-CHL-6	Extruded channel. Includes snap-on frosted lens with mounting clips and screws.	6’	
LED-CHL-AMC	(2) Adjustable mounting brackets for LED-CHL	N/A	
LED-CHL-EC	(2) End caps for LED-CHL - one solid, one with hole.	N/A	
LED-CHL-MC	(2) Additional mounting clips for LED-CHL	N/A	


45° MINI ANGLE MOUNT

LED-CHL-45-MINI	Extruded angled (45°) silver channel. Includes snap-on white lens with (2) mounting clips and (2) screws.	4'	
LED-CHL-45-MINI-B	Extruded angled (45°) black channel. Includes snap-on white lens with (2) mounting clips and (2) screws.	4'	
LED-CHL-45-MINI-EC	(2) End caps for LED-CHL-45-MINI: light gray, one solid, one with hole	N/A	
LED-CHL-45-MINI-EC-B	(2) End caps for LED-CHL-MINI-B: black, one solid, one with hole	N/A	
LED-CHL-45-MINI-MC	(2) Mounting clips and (2) screws for LED-CHL-45-MINI	N/A	
LED-CHL-45-M-LENS-BK	Lens in black for LED-CHL-45-MINI	4'	

BENDABLE

LED-CHL-BND-4	Extruded 4’ bendable channel. Inc. snap-on frosted lens with screws	4’	
LED-CHL-BND-6	Extruded 6’ bendable channel. Inc. snap-on frosted lens with screws	6’	
LED-CHL-BND-EC	(2) end caps for LED-CHL-BND 4’ or 6’	N/A	
LED-CHL-BND-MC	(2) mounting clips and screws for LED-CHL-BND 4’ or 6’	N/A	


SLIM

LED-CHL-SLIM	Slim Channel, snap on white lens with mounting clips and screws	4’	
LED-CHL-SLIM-BRACKETS	(2) Mounting clips and screws for LED-CHL-SLIM	N/A	
LED-CHL-SLIM-EC	(2) End caps - one solid, one with wiring hole	N/A	

©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice
18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net

SHWC LUXCONTROL WIFI CONTROLLER

NOTE: Power supply **MUST NOT BE DIMMED** at the input to properly power the controls.




©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice

18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net

SHWC LUXCONTROL WIFI CONTROLLER WITH POWER REPEATER


NOTE: Power supply **MUST NOT BE DIMMED** at the input to properly power the controls.




©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice

18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net

SHWD LUXCONTROL WIFI DIMMER




SWITCHLD SWD DRIVER AND DIMMER



RF CONTROLLER

Incoming power for (L N G) options can be 120V or 277V.
Check power supply for proper input voltage and output power required.
Power Supply output voltage must match LED operating voltage. (24VDC)
Power supply used **MUST NOT BE DIMMED** at the input to properly power the controls.
See Controller instructions for pairing and wiring details.



HC-RF-UNV-5CH
RF Remote Control

Note: Requires 2x 1.5V AAA batteries (not included)

*Multiple power supplies can be replaced with a single multi-output power supply.

Example: (3) **LD-XD-UNV96-24** can be replaced by (1) **LD-XD-UNV300-24**

©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice


18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net

LTR-P Professional Series

4.5W, 24VDC LED Tape
Specification Sheet


GMLighting®

RF REMOTE CONTROLLER AND REPEATER




CM-RF-UNV-5CH
RF Controller

DIMENSIONS




CM-RF-UNV-5CH
RF Controller



RPT-UNV-5CH
Repeater Amplifier

©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice
18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net

RF HAND HELD REMOTE FEATURES AND DIMENSIONS



©2026 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice

18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net