

LTR-S Specification Series

DTW (Dim to Warm) LED Tape Specification Sheet

GMLighting®


PRODUCT OVERVIEW

Dim to warm provides color dimming that goes from 3500K to 1800K. This is true ambient dimming that is made possible via the double cluster of diodes that dissolve into each other when dimmed. DTW tape mimics incandescent dimming. Available in 16'4" (5 meter) reels.

FEATURES

- 24VDC
- Dims from 3500K to 1800K
- Dry location
- Cuttable every 3"
- Custom lengths available - consult factory
- Premium diode pairs
- 120° viewing angle
- Dimmable
- 3M adhesive back
- Maximum run on a given lead is 32'-8"
- Includes (3) Sure-Tite connectors

Project Name	Type
Catalog #	Date



SPECIFICATIONS

ELECTRICAL

- 24V
- 2.8 watts per foot

OPTICS

- 95+ CRI

OPERATING TEMP

- -4°F to 122°F

CERTIFICATION

- ETL
- Class 2
- Closet Rated. Compliant with NFPA 70, NEC section 410.16 (A)(3) and 410.16 (C)(5)

WARRANTY

- 5-year warranty when paired with GM power supply.

Note: Dims with magnetic drivers and MLV switches. Not compatible with SwitchLD

ORDERING INFORMATION

Example: LTR-S-DTW-24V-3.0W-16

Model	-	Series	-	Type	-	Voltage	-	Wattage	-	Reel Length
LTR	-	S	-	DTW	-	24V	-	3.0W	-	16

*Reel Length: 16 = 16'-4"

ACCESSORIES

Model	Description
ESTC-1	Sure-Tite tape to tape connector
ESTC-90	Sure-Tite 90° connector
ESTLK-60	Sure-Tite 60" adjustable tape to tape connector
ESTW-60	Sure-Tite 60" adjustable tape to power connector
ESTW-CO	Sure-Tite tape to power supply connector (no wire)


LTR-S Specification Series

DTW (Dim to Warm) LED Tape Specification Sheet

GMLighting®

Catalog No.	Length	Lumens @ 3500K	CRI	Color Temp.	Max. Run
LTR-S-DTW-24V-3.0W-16	16'-4" / 5M	194	95+	1800K - 3500K	32'-8"
Includes 24" lead affixed to tape and (3) ESTW-60 Sure-Tite connectors. Kelvin temperature (color) ±100K.					

DIMENSION



RECOMMENDED DRIVERS

Catalog No.	Description	Watts	Weight	Dimensions
LD-MD-UNV30	12VDC / 24VDC - 30W - 120V or 277V 12V/2.5A - 24V/1.25A - Class 2 Auto reset.	30W	2.4 lbs.	8.27" L x 2.5" W x 1.95" H
LD-MD-UNV60	12VDC / 24VDC - 60W - 120V or 277V 12V/5A - 24V/2.5A - Class 2 Auto reset.	60W	4.4 lbs	8.86" L x 3.31" W x 2.89" H
LD-MD-UNV96-24	24VDC - 96W - 120V or 277V 24V/4A - Class 2 Auto reset.	96W	5.2 lbs	8.86" L x 3.31" W x 2.89" H
LD-MD-UNV150-12	12VDC - 150W - 120V or 277V 24V/4A - Class 2 Auto reset.	150W	9.1 lbs	11.02" L x 4.88" W x 3.62" H
LD-MD-UNV200-24	24VDC - 200W - 120V or 277V 24V/4A - Class 2 Auto reset.	200W	9.9 lbs	11.02" L x 4.88" W x 3.62" H
LD-MD-UNV300-24	24VDC - 300W - 120V or 277V 24V/4A - Class 2 Auto reset.	300W	10.6 lbs	11.02" L x 4.88" W x 3.62" H

Please see our website for updated power supply specifications and information.

LTR-S Specification Series


DTW (Dim to Warm) LED Tape Specification Sheet

GMLighting®

COMPATIBLE CHANNELS - (fits connectors on pg. 1)


EXTRA DEEP

Catalog No.	Description	Length	Dimensions
LED-CHL-XD	Extra deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4'	
LED-CHL-XD-6	Extra deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	6'	
LED-CHL-XD-AMC	(2) Adjustable mounting brackets for LED-CHL-XD	N/A	
LED-CHL-XD-EC	(2) End caps for LED-CHL-XD. One solid, one with hole.	N/A	
LED-CHL-XD-MC	(2) Mounting clips and screws for LED-CHL-XD	N/A	




EXTRA DEEP FLANGED

LED-CHL-XD-F	Extra deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	4'	
LED-CHL-XD-F-6	Extra deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	6'	
LED-CHL-XD-F-DC	(2) Drywall mounting brackets for LED-CHL-XD-F	N/A	
LED-CHL-XD-F-EC	(2) End caps for LED-CHL-XD-F. One solid, one with hole.	N/A	




MINI DEEP

LED-CHL-XD-MD	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4'	
LED-CHL-XD-MD-WH	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws. White.	4'	
LED-CHL-XD-MD-B	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws. Black.	4'	
LED-CHL-XD-MD-6	Mini deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	6'	
LED-CHL-XD-MD-6-WH	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws. White.	6'	
LED-CHL-XD-MD-6-B	Mini deep format extruded channel. Includes snap-on frosted lens with mounting clips and screws. Black.	6'	
LED-CHL-XD-MD-AMC	(2) Adjustable mounting brackets for LED-CHL-XD-MD	N/A	
LED-CHL-XD-MD-EC	(2) End caps for LED-CHL-XD-MD. One solid, one with hole.	N/A	
LED-CHL-XD-MD-MC	(2) Mounting clips for LED-CHL-XD-MD	N/A	



MINI DEEP FLANGED

LED-CHL-XD-MD-F	Mini deep format flanged extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	4'	
LED-CHL-XD-MD-F-WH	Mini deep format flanged extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws. White.	4'	
LED-CHL-XD-MD-F-B	Mini deep format flanged extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws. Black.	4'	
LED-CHL-XD-MD-F-6	Mini deep format extruded flanged channel with flange. Includes snap-on frosted lens with mounting clips and screws.	6'	
LED-CHL-XD-MD-F-6-WH	Mini deep format extruded flanged channel with flange. Includes snap-on frosted lens with mounting clips and screws. White.	6'	
LED-CHL-XD-MD-F-6-B	Mini deep format extruded flanged channel with flange. Includes snap-on frosted lens with mounting clips and screws. Black.	6'	
LED-CHL-XD-MD-F-DC	(2) Drywall mounting brackets for LED-CHL-XD-MD-F	N/A	
LED-CHL-XD-MD-F-EC	(2) End caps for LED-CHL-XD-MD-F. One solid, one with hole.	N/A	



LTR-S Specification Series

DTW (Dim to Warm) LED Tape Specification Sheet

GMLighting®

COMPATIBLE CHANNELS cont. - (fits connectors on pg. 1)

45° ANGLE MOUNT

Catalog No.	Description	Dimensions
LED-CHL-45	Extruded angled (45°) channel. Includes snap-on frosted lens with mounting clips and screws.	4'
LED-CHL-45-EC	(2) End caps for LED-CHL-45 - one solid, one with hole	N/A
LED-CHL-45-MC	(2) Mounting clips and screws for LED-CHL-45	N/A

45° LARGE ANGLE MOUNT

LED-CHL-45-1200	Extruded angled (45°) channel. Includes snap-on frosted lens with mounting clips and screws.	4'
LED-CHL-45-1200-EC	(2) End caps for LED-CHL-45 - one solid, one with hole	N/A
LED-CHL-45-1200-MC	(2) Additional mounting clips for LED-CHL-45-1200	N/A

WIDE

LED-CHL-W	Wide format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4'
LED-CHL-W-6	Wide format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	6'
LED-CHL-W-AMC	(2) Adjustable mounting brackets for LED-CHL-W	N/A
LED-CHL-W-EC	(2) End caps for LED-CHL-W - one solid, one with hole.	N/A
LED-CHL-W-MC	(2) Additional mounting clips for LED-CHL-W	N/A

MUD IN - STANDARD

LED-CHL-MI-ST6	Standard extruded aluminum mud-in channel. Includes snap-on frosted lens.	6'
LED-CHL-MI-ST-EC	(2) End caps for LED-CHL-MI-ST6 one solid, one with hole.	N/A

STANDARD STRAIGHT

LED-CHL2-4-CA	Silver channel, white lens (2) mounting clips, (2) screws	4'
LED-CHL2-4-WH	White channel, white lens (2) mounting clips, (2) screws	4'
LED-CHL2-4-BK	Black channel, white lens (2) mounting clips, (2) screws	4'
LED-CHL2-6-CA	Silver channel, white lens, (4) mounting clips, (4) screws	6'
LED-CHL2-6-WH	White channel, white lens, (4) mounting clips, (4) screws	6'
LED-CHL2-6-BK	Black channel, white lens, (4) mounting clips, (4) screws	6'
LED-CHL2 LENS-4-BK	Lens in black for LED-CHL2-4	4'
LED-CHL2 LENS-6-BK	Lens in black for LED-CHL2-6	6'
LED-CHL2-ECG	(2) End caps for LED-CHL2-CA: light gray, one solid, one with hole	N/A
LED-CHL2-ECW	(2) End caps for LED-CHL2-WH: white, one solid, one with hole	N/A
LED-CHL2-EBC	(2) End caps for LED-CHL2-BK: black, one solid, one with hole	N/A
LED-CHL2-MC	(2) Mounting clips and (2) screws	N/A
LED-CHL2-AMC	(2) Adjustable mounting clips and (2) screws	N/A

LTR-S Specification Series


DTW (Dim to Warm) LED Tape Specification Sheet

GMLighting®

COMPATIBLE CHANNELS - SOLDERED LEADS ONLY

STANDARD STRAIGHT

Catalog No.	Description	Dimensions
LED-CHL	Extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4'
LED-CHL-6	Extruded channel. Includes snap-on frosted lens with mounting clips and screws.	6'
LED-CHL-AMC	(2) Adjustable mounting brackets for LED-CHL	N/A
LED-CHL-EC	(2) End caps for LED-CHL - one solid, one with hole.	N/A
LED-CHL-MC	(2) Additional mounting clips for LED-CHL	N/A



45° MINI ANGLE MOUNT

LED-CHL-45-MINI	Extruded angled (45°) silver channel. Includes snap-on white lens with (2) mounting clips and (2) screws.	4'
LED-CHL-45-MINI-B	Extruded angled (45°) black channel. Includes snap-on white lens with (2) mounting clips and (2) screws.	4'
LED-CHL-45-MINI-EC	(2) End caps for LED-CHL-45-MINI: light gray, one solid, one with hole	N/A
LED-CHL-45-MINI-EC-B	(2) End caps for LED-CHL-MINI-B: black, one solid, one with hole	N/A
LED-CHL-45-MINI-MC	(2) Mounting clips and (2) screws for LED-CHL-45-MINI	N/A
LED-CHL-45-M-LENS-BK	Lens in black for LED-CHL-45-MINI	4'

