

# NeoVision24 TopFlex

## Flexible Neon LED Tape Specification Sheet

Project Name	Type
Catalog #	Date

### PRODUCT OVERVIEW

A 24VDC high transmission, flexible linear 'neon' tape that is field cuttable and joinable. Designed for applications that require ultra-rich light and color saturation that is characteristic of neon. TopFlex enables vertical bending that conforms tape around curvilinear surfaces.



### FEATURES

- Multiple power feed options
- Tape encased in UV stable silicone (UV protected)
- Wireless control with LUXcontrol App and controller
- 2700K, 3000K, 4000K / Amber, Blue, Green or Red
- 120° viewing angle
- Maximum run: 32'-8"
- Cuttable and joinable in two inch increments
- Each run requires an end cap (sold separately)
- No tools required for capping and joining
- Mounting clips included (recommend use one per foot)

### SPECIFICATIONS

#### ELECTRICAL

- 24VDC
- 3W per foot

#### PHOTOMETRIC

- 90+ CRI

#### AMBIENT OPERATING TEMP

- -13°F - 131°F

#### CERTIFICATION

- UL
- IP65

#### WARRANTY

- 5 years when paired with GM power supply



### ORDERING INFORMATION

#### White

Product No.	Length	Lumens/ft	Color Temp
NV24T-3W-27K-16	16'-4"	218lm	2700K
NV24T-3W-27K-32	32'-8"	218lm	2700K
NV24T-3W-30K-16	16'-4"	230lm	3000K
NV24T-3W-30K-32	32'-8"	230lm	3000K
NV24T-3W-40K-16	16'-4"	217lm	4000K
NV24T-3W-40K-32	32'-8"	217lm	4000K


#### Colors

Product No.	Length	Lumens/ft	Color Temp
NV24T-3W-AM-16	16'-4"	N/A	Amber
NV24T-3W-AM-32	32'-8"	N/A	Amber
NV24T-3W-BL-16	16'-4"	N/A	Blue
NV24T-3W-BL-32	32'-8"	N/A	Blue
NV24T-3W-GR-16	16'-4"	N/A	Green
NV24T-3W-GR-32	32'-8"	N/A	Green
NV24T-3W-RD-16	16'-4"	N/A	Red
NV24T-3W-RD-32	32'-8"	N/A	Red

Max Run: 32'-8"

Kelvin temperature (color) ±100K.

NOTE: Every reel includes (1) NV24T-PF-EF (tape-to-power feed with 48" of lead). 16' reel includes (16) NV24T-MC-A mounting clips and screws. 32' reel comes with (32) NV24T-MC-A mounting clips and screws.



TopFlex Cutaway

# NeoVision24 TopFlex

## Flexible Neon LED Tape Specification Sheet




### CONNECTORS AND ACCESSORIES


Product No.	Description
NV24T-PF-EF8	Tape-to-Power Flexible End Feed, 8 ft.
NV24T-PF-BF8	Tape-to-Power Flexible Bottom Feed, 8 ft.
NV24T-SP	Tape-to-Tape Splice Connector
NV24T-CHL-A4	Aluminum Channel, 4 ft.
NV24T-CHL-A6	Aluminum Channel, 6 ft.
NV24T-MC-A	Aluminum Mounting Clips (set of 20)

Product No.	Description
NV24T-TTC6	Tape-to-Tape Flexible Connector, 6"
NV24T-TTC12	Tape-to-Tape Flexible Connector, 12"
NV24T-TTC24	Tape-to-Tape Flexible Connector, 24"
NV24T-FLEX-CHL	Flexible Mounting Channel, 39.5"
NV24T-EC	End Cap
NV24-CT	Tape Cutting Tool

The above connectors, channels, mounting clips and caps are for the exclusive use of **NeoVision24 TopFlex Neon Tape** and are ordered separately.



### Tape Configuration Example




# NeoVision24 TopFlex

## Flexible Neon LED Tape Specification Sheet




### DIMENSIONS


NV24T-PF-EF8




NV24T-PF-BF8




NV24T-SP




NV24T-EC




NV24T-CHL-A4 (4' L)  
NV24T-CHL-A6 (6' L)




NV24T-MC-A




NV24T-FLEX-CHL



NV24S-TTC6 | NV24S-TTC12 | NV24S-TTC24



### TopFlex Tape




# NeoVision24 TopFlex

## Flexible Neon LED Tape Specification Sheet





### WIRING DIAGRAM

#### Single Color Smart Controller



#### Repeater Wiring Single color connection - One channel



### CONTROLLERS

Product No.	Description
SHWC*	Smart 2.4 GHz WiFi Controller, Standard 12V/24V Low Voltage, 1-Channel / 2-Wire
SHWC-RGBW-RPT*	Universal Smart Power Repeater

### POWER SUPPLIES

Product No.	Description
LD-XD Series	LineDRIVE 24V Dimmable Power Supplies
LD-MD Series	LineDRIVE 24V Magnetic Power Supplies
PSD Series	Constant Voltage 24V Dimmable Power Supplies




\*NOTE: For use with LD-E (non-dimmable) or LD-XD (dimmable) power supply only.  
Not compatible with LD-MD (magnetic) power supply.

# NeoVision24 TopFlex

## Flexible Neon LED Tape Specification Sheet

### SHWC LUXCONTROL WIFI CONTROLLER


**GROUP MULTIPLE  
CONTROLLERS IN THE  
LUXCONTROL APP**



# NeoVision24 TopFlex

## Flexible Neon LED Tape Specification Sheet


### SHWC LUXCONTROL WIFI CONTROLLER WITH POWER REPEATER



# NeoVision24 TopFlex


## Flexible Neon LED Tape Specification Sheet

### SHWD LUXCONTROL WIFI CONTROLLER



### SHWD SWD DRIVER AND DIMMER

**SWITCHLD - SWD**  
12VDC or 24VDC  
12V - 48W MAX LOAD  
24V - 80W MAX LOAD




# NeoVision24 TopFlex



## Flexible Neon LED Tape Specification Sheet

### RF CONTROLLER

Incoming power for (L N G) options can be 120V or 277V.  
 Check power supply for proper input voltage and output power required.  
 Power Supply output voltage must match LED operating voltage. (24VDC)  
 Power supply used **MUST NOT BE DIMMED** at the input to properly power the controls.  
 See Controller instructions for pairing and wiring details.



### CONTROLLERS

Product No.	Description
HC-RF-UNV-5CH	Universal 1-5 Channel RF Remote Control
CM-RF-UNV-5CH	Universal 1-5 Channel Control Module
RPT-UNV-5CH	Universal 1-5 Channel Repeater Amplifier

Note: Multiple power supplies can be replaced with a single multi-output power supply.

### POWER SUPPLIES

Product No.	Description
LD-E-UNV Series	LineDRIVE 12V / 24V Non-Dimmable Power Supplies
LD-XD-UNV Series	LineDRIVE 12V / 24V Power Supplies
LTP Series	24V Electronic LED Power Supplies



# NeoVision24 TopFlex

## Flexible Neon LED Tape Specification Sheet



### RF HAND HELD REMOTE FEATURES AND DIMENSIONS

