

RSD LED Downlight

120V Selectable White Regressed Slim Downlight



Project Name	Type
Catalog #	Date

PRODUCT OVERVIEW

Easy to install with an included junction box that is connected via a modular jack. This 3" slim mount, regressed downlight features superior optics along with a Title 24 rating in a streamlined, shallow mount design.

FEATURES

- 120V
- Selectable: 2700K, 3000K, 4000K
- Wet location
- IC rating for insulated ceilings
- Edge-Lit technology for diode free illumination
- Meets NEC code Article 314.16 for junction box fill of (5) 14 AWG or (5) 12 AWG max.
Box volume = 11.25in³

SPECIFICATIONS

ELECTRICAL	LABEL
• 120V	• ETL
• 6W	• Title 24 - JA8
OPTICS	WARRANTY
• 90+ CRI	• 5 years
• 120° beam angle	



ORDERING INFORMATION

Example: RSD-3-TUN-WH

Model	-	Diameter	-	Color Temp	-	Finish
RSD		3 (3-3/4" Diam)		TUN		WH (White)

CONNECTORS AND ACCESSORIES

Model	Description
RSD-5FT-EXT	5' Extension Cord for RSD Series Downlights
RSD-10FT-EXT	10' Extension Cord for RSD Series Downlights
RSD-20FT-EXT	20' Extension Cord for RSD Series Downlights
UNV-NCP	New Construction Plate for All RSD Series Downlights



NCP-6



UNV-NCP

RSD LED Downlight

120V Selectable White Regressed Slim Downlight



Catalog No.	Diameter	Selectable Color Temp	Wattage	Lumens	Finish
RSD-3-TUN-WH	3 (3-3/4" Dia.)	2700K/3000K/4000K	6W	400, 425, 450	White

WIRING DIAGRAMS

