GMLighting®

LED Tape Channel Guide



LED TAPE STANDARD MOUNTING CHANNELS

PRODUCT DESCRIPTION

GM Lighting's aluminum channels accepts all GM Lighting LEDTask flexible LED Linear tape. Perfect for installations that require a rigid extruded channel that the LED tape can be mounted into. The new **LED-CHL2** standard channel has an updated designed to seamlessly integrate with most low voltage GM Lighting LED tapes and EST connectors for easy installation.




LED-CHL2-4-BK with black lens cover (LED-CHL2-LENS-4-BK)



LED-CHL-EC end cap with hole and LED-CHL-MC mounting clips





Optional LED-CHL-AMC adjustable mounting bracket attached to LED-CHL

		MOUNTING CHANI	CHANNEL COMPATIBLE TAPE		
	Catalog No.	Description	Length	Dimensions	Tape and Connectors
RUN	LED-CHL	Extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4'		LTR-P Professional Series (Dry Location) and No Connectors
STANDARD STRAIGHT RUN	LED-CHL-6	Extruded channel. Includes snap-on frosted lens with mounting clips and screws.	6'	.400"	LTR-E Economy Series and ST Connectors
	LED-CHL-EC	(2) End caps for LED-CHL: one solid, one with hole	N/A		LTR-S Specification Series (Single Color) and No Connectors
STANDA	LED-CHL-AMC	(2) Adjustable mounting brackets for LED-CHL	N/A	 ← .675"→ 	
•	LED-CHL-MC	(2) Mounting clips and screws for LED-CHL	N/A		LTR-S-COB (Chip in Board) and No Connectors
	LED-CHL2-4-BK	Straight Black Channel, Snap-on White Lens with Mounting Clips and Screws	4'		ITD D Desfectional Cosine (Devil agetical and FCT Comparture
	LED-CHL2-4-CA	Straight Silver Channel, Snap-on White Lens with Mounting Clips and Screws	4'	.5"	LTR-P Professional Series (Dry Location) and EST Connectors
	LED-CHL2-4-WH	Straight White Channel, Snap-on White Lens with Mounting Clips and Screws	4'		
0N 2	LED-CHL2-6-BK	Straight Black Channel, Snap-on White Lens with Mounting Clips and Screws	6'		LTR-E Economy Series and ST Connectors
V VERSI	LED-CHL2-6-CA	Straight Silver Channel, Snap-on White Lens with Mounting Clips and Screws	6'		
STANDARD STRAIGHT RUN VERSION 2	LED-CHL2-6-WH	Straight White Channel, Snap-on White Lens with Mounting Clips and Screws	6'		LTR-S Specification Series (Single Color) and EST Connectors
TRAIG	LED-CHL2-LENS-4-BK	Black Lens Cover	4'	\	
DARD S	LED-CHL2-LENS-6-BK	Black Lens Cover	6'	.69"	
STAN	LED-CHL2-ECB	(2) Black End Caps: 1 Solid, 1 with Hole	N/A		LTR-S-COB (Chip in Board) and EST Connectors
	LED-CHL2-ECG	(2) Gray End Caps: One Solid, One with Hole	N/A		, , , , , , , , , , , , , , , , , , ,
	LED-CHL2-ECW	(2) White End Caps: One Solid, One with Hole	N/A		
	LED-CHL2-AMC	(2) Adjustable Mounting Brackets	N/A		LTR-S-TUN (Tunable White) and No Connectors
	LED-CHL2-MC	(2) Mounting Clips and Screws	N/A		

LED TAPE 45° MOUNTING CHANNELS

PRODUCT DESCRIPTION


45° format mounting channels are the perfect vessel that not only insures an architectural quality installation that focuses light distribution at a 45° angle, but also minimizes diode imaging due to the frosted lens that is included with each channel.



LED-CHL-45-MINI-B



LED-CHL-45-1200-EC end caps either solid or with a wiring hole



LED-CHL-45-M-LENS-BK optional black lens cover for LED-CHL-45-MINI



45° format channels are perfect for angled light distribution and tight corner applications

LTR-S-COB-WP (Wet Location) and Connectors

			аррионного		
		MOUNTING CHANN	IEL		CHANNEL COMPATIBLE TAPE
	Catalog No.	Description	Length	Dimensions	Tape and Connectors
	LED-CHL-45-MINI	Extruded angled (45°) channel. Includes snap-on frosted lens with mounting clips and screws.	4'		LTR-P Professional Series (Dry Location) and No Connectors
TNO	LED-CHL-45-MINI-B	Extruded angled (45°) black channel.	4'		LTR-E Economy Series and No Connectors
MINI 45° ANGLE MOUNT	LED-CHL-45-MINI-EC	(2) End caps for LED-CHL-45-MINI: one solid, one with hole	N/A	.39"	LTR-S Specification Series (Single Color) and No Connectors
45° ANG	LED-CHL-45-MINI-EC-B	(2) End caps for LED-CHL-MINI-B: one solid, one with hole	N/A		LTR-S-TUN (Tunable White) and No Connectors
MINI	LED-CHL-45-MINI-MC	(2) Mounting clips and screws for LED-CHL-45-MINI	N/A	→ .63" ←	LTR-S-DTW (Dim to Warm) and No Connectors
	LED-CHL-45-M LENS BK	Lens Cover in black for LED-CHL-45-MINI	4'		LTR-S-COB (Chip on Board) and No Connectors
	LED-CHL-45	Extruded angled (45°) channel. Includes snap-on frosted lens	4'	/	LTR-P Professional Series (Dry Location) and EST Connectors
		with mounting clips and screws.		.53"	LTR-E Economy Series and ST Connectors
45° ANGLE MOUNT	LED-CHL-45-EC	(2) End caps for LED-CHL-45: one solid, one with hole	N/A	.53 .825"	LTR-S Specification Series (Single Color) and EST Connectors
E		one sond, one with note			LTR-S-COB (Chip on Board) and EST Connectors
ANG		(2) Mounting clips and screws for LED-CHL-45	N/A		LTR-S-DTW (Dim to Warm) and EST Connectors
45°	LED-CHL-45-MC				LTR-S-RGBW and EZ Connectors
	LED-CHL-43-MC				LTR-S-TUN (Tunable White) and LTR-S-TUN Connectors
					LTR-S-COB-24V-RGBTW and LOC6 Connectors
		Extruded angled (45°) channel.			LTR-P Professional Series (Dry Location) and EST Connectors
—	LED-CHL-45-1200	Includes snap-on frosted lens with mounting clips and screws.	4'		LTR-E Economy Series and ST Connectors
		with mounting clips and screws.			LTR-S Specification Series (Single Color) and EST Connectors
E E	LED-CHL-45-1200-EC	(2) End caps for LED-CHL-45:	N/A	1.65"	LTR-S-COB (Chip on Board) and EST Connectors
ANG	225 0112 10 1200 20	one solid, one with hole		90°	LTR-S-DTW (Dim to Warm) and EST Connectors
LARGE 45° ANGLE MOUNT					LTR-P-WP (WetLocation) and Connectors
5	LED-CHL-45-1200-MC	(2) Additional mounting clips for LED-CHL-45-1200	N/A	1.18"	LTR-S-RGBW / LTR-S-RGBW-WP (Dry or Wet Location) and Connectors
		101 220-0112-70-1200			LTR-S-TUN (Tunable White) and LTR-S-TUN Connectors


LED TAPE DEEP-SET MOUNTING CHANNELS

PRODUCT DESCRIPTION

Extra Deep and Mini Deep aluminum mounting channels are the perfect vessel that not only insures an architectural quality installation, but also minimizes diode imaging due to the frosted lens that is included with each channel.



LED-CHL-XD-AMC adjustable mounting bracket for Extra-Deep Channels



LED-CHL-XD-EC end cap without hole for deepset channels




LED-CHL-XD-MD-B

		MOUNTING CHANN	CHANNEL COMPATIBLE TAPE		
	Catalog No.	Description	Length	Dimensions	Tape and Connectors
	LED-CHL-XD	Extra-Deep Channel, Snap-on White Lens with Mounting Clips and Screws	4'		LTR-P / LTR-P-WP Professional Series (Dry or Wet Location) and Connectors LTR-E Economy Series and ST Connectors
	LED-CHL-XD-6	Extra-Deep Channel, Snap-on White Lens with Mounting Clips and Screws	6'	.79"	LTR-S Specification Series (Single Color) and EST Connectors LTR-S-COB / LTR-S-COB-WP (Dry or Wet Location) and Connectors
EXTRA-DEEP	LED-CHL-XD-EC	(2) End Caps: One Solid, One with Hole	N/A		LTR-S-DTW (Dim to Warm) and EST Connectors LTR-S-RGBW (dry Location) and EZ Connectors
	LED-CHL-XD-AMC	(2) Adjustable Mounting Brackets	N/A	.98"	LTR-S-TUN (Tunable White) and LTR-S-TUN Connectors LTR-S-COB-24V-RGBTW and LOC6 Connectors
	LED-CHL-XD-MC	(2) Mounting Clips and Screws	N/A		LTR-P-WP (WetLocation) and Connectors LTR-S-RGBW / LTR-S-RGBW-WP (Dry or Wet Location) and Connectors
	LED-CHL-XD-MD	Mini-Deep Channel, Snap-on White Lens with Mounting Clips and Screws	4'		LTR-P Professional Series (Dry Location) and EST Connectors
	LED-CHL-XD-MD-B	Mini-Deep Black Channel, Snap-on White Lens with Mounting Clips and Screws	4'		LTR-E Economy Series and ST Connectors
	LED-CHL-XD-MD-WH	Mini-Deep White Channel, Snap-on White Lens with Mounting Clips and Screws	4'		LTR-5 Specification Series (Single Color) and EST Connectors
<u>a</u>	LED-CHL-XD-MD-6	Mini-Deep Channel, Snap-on White Lens with Mounting Clips and Screws	6'	↑ }_ 550" √	
MINI-DEEP	LED-CHL-XD-MD-6-B	Mini-Deep Black Channel, Snap-on White Lens with Mounting Clips and Screws	6'	.62"	LTR-S COB (Chip On Board) and EST Connectors
	LED-CHL-XD-MD-6-WH	Mini-Deep White Channel, Snap-on White Lens with Mounting Clips and Screws	6'		LTR-S-DTW (Dim to Warm) and EST Connectors
	LED-CHL-XD-MD-EC	(2) End Caps: One Solid, One with Hole	N/A		LTR-S-RGBW (Dry Location) and EZ Connectors
	LED-CHL-XD-MD-AMC	(2) Adjustable Mounting Brackets	N/A		INDEXING ALL MANAGEMENT
	LED-CHL-XD-MD-MC	(2) Mounting Clips and Screws	N/A		LTR-S-TUN (Tunable White) and LTR-S-TUN Connectors

LED TAPE FLANGED MOUNTING CHANNELS

PRODUCT DESCRIPTION

GM Lighting's flanged aluminum mounting channels are the perfect vessel that not only insure an architectural quality installation, but also minimize diode imaging due to the frosted lens that is included with each channel.



LED-CHL-XD-F channel is perfect for wet location and RGB tapes



LED-CHL-XD-MD-F-6-WH



Drywall spring clips and adjustable brackets enable custom installations

		MOUNTING CHANN	CHANNEL COMPATIBLE TAPE		
	Catalog No.	Description	Length	Dimensions	Tape and Connectors
	LED-CHL-XD-MD-F	Mini deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	4'		LTR-P Professional Series (Dry Location) and EST Connectors
	LED-CHL-XD-MD-F-WH	Mini deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws. White.	4'		LTR-E Economy Series and ST Connectors
ED	LED-CHL-XD-MD-F-B	Mini deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws. Black.	4'		LTR-S Specification Series (Single Color) and EST Connectors
MINI DEEP FLANGED	LED-CHL-XD-MD-F-6	Mini deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	6'	.625" 3" .55"	LTR-S COB (Chip On Board) and EST Connectors
MINI DE	LED-CHL-XD-MD-F-6-WH	Mini deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws. White.	6'		LTR-S-DTW (Dim to Warm) and EST Connectors
	LED-CHL-XD-MD-F-6-B	Mini deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws. Black.	6'		LTR-S-RGBW (Dry Location) and EZ Connectors
	LED-CHL-XD-MD-F-DC	(2) Drywall mounting brackets for LED-CHL-XD-MD-F	N/A		
	LED-CHL-XD-MD-F-EC	(2) End caps for LED-CHL-XD-MD-F One solid, one with hole.	N/A		LTR-S-TUN (Tunable White) and LTR-S-TUN Connectors
		Extra deep format extruded channel with flange. Includes snap-on frosted lens with mounting clips and screws.	4'		LTR-P Professional Series (Dry Location) and EST Connectors
					LTR-E Economy Series and ST Connectors
				4.5"	LTR-S Specification Series (Single Color) and EST Connectors
IGED	LED-CHL-XD-F-6	Extra deep format extruded channel with flange. Includes snap-on frosted lens with	6'	1.5" ————————————————————————————————————	LTR-S-COB / LTR-S-COB-WP (Dry or Wet Location) and Connectors
EXTRA DEEP FLANGED		mounting clips and screws.		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	LTR-S-DTW (Dim to Warm) and EST Connectors
A DEE				\ \ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	LTR-S-RGBW (dry Location) and EZ Connectors
EXTR		(2) Drywall mounting brackets for LED-CHL-XD-F	N/A	.98"	LTR-S-TUN (Tunable White) and LTR-S-TUN Connectors
					LTR-S-COB-24V-RGBTW and LOC6 Connectors
	LED-CHL-XD-F-EC	(2) End caps for LED-CHL-XD-F. One solid, one with hole.	N/A		LTR-P-WP (WetLocation) and Connectors
	OI				LTR-S-RGBW / LTR-S-RGBW-WP (Dry or Wet Location) and Connectors

LED TAPE WIDE, SLIM & FLEXIBLE MOUNTING CHANNELS

KEY FEATURES

- · Aluminum extrusions in 4' and 6' lengths
- Each channel comes complete with lens and mounting hardware
- · Accessories designed for channel come right after channel listing



Choice of widths and positions assures a fit for all GM LED Linear Tape - dry and wet location



LED-CHL-BND enables LED tape to follow curves and bends while being protected by flexible frosted lens



		MOUNTING CHAN	CHANNEL COMPATIBLE TAPE		
	Catalog No.	Description	Length	Dimensions	Tape and Connectors
	LED-CHL-BND	Extruded bendable channel. Includes snap-on frosted lens with mounting clips and screws.	4'		LTR-P Professional Series (Dry Location) and No Connectors LTR-E Economy Series and No Connectors
BENDABLE	LED-CHL-BND-6	Extruded bendable channel. Includes snap-on frosted lens with mounting screws.	6'	<u>1.233"</u> ←70"→	LTR-S Specification Series (Single Color) and No Connectors LTR-S-DTW (Dim to Warm) and No Connectors
	LED-CHL-BND-EC	(2) End caps for LED-CHL-BND: one solid, one with hole.	N/A		IXD C COR (Chin Co Pound and No Company)
	LED-CHL-BND-MC	(2) Mounting clips and screws for LED-CHL-BND	N/A		LTR-S COB (Chip On Board) and No Connectors
					LTR-P Professional Series (Dry Location) and No Connectors
	LED-CHL-SLIM	Extruded slim channel. Includes snap-on frosted lens with mounting clips and screws	4'	→ .55" ←	LTR-E Economy Series and No Connectors
SLIM				.25"	LTR-5 Specification Series (Single Color) and No Connectors
장	LED-CHL-SLIM- BRACKETS	(2) Mounting brackets for LED-CHL-SLIM	N/A	.674" - 1	LTR-S-DTW (Dim to Warm) and No Connectors
	LED-CHL-SLIM-EC	(2) Solid end caps for LED-CHL-SLIM	N/A		LTR-S COB (Chip On Board) and No Connectors
	LED-CHL-W	Wide format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	4'		LTR-P Professional Series (Dry Location) and EST Connectors LTR-E Economy Series and ST Connectors
	LED-CHL-W-6	Wide format extruded channel. Includes snap-on frosted lens with mounting clips and screws.	6'		LTR-S Specification Series (Single Color) and EST Connectors LTR-S-COB (Chip on Board) and EST Connectors
w	LED-CHL-W-AMC	(2) Adjustable mounting brackets for LED-CHL-W	N/A		LTR-S-DTW (Dim to Warm) and EST Connector
WIDE	LED-CHL-W-EC	(2) End caps for LED-CHL-W:	N/A	1.019" → .45/"	LTR-S-RGBW (dry Location) and EZ Connectors
	LLD-CHL-W-LC	one solid, one with hole.	170	1.019	LTR-S-TUN (Tunable White) and LTR-S-TUN Connectors
		(2) Additional mounting clips for LED- CHL-45-1200	N/A		LTR-P-WP (Wet Location) and No Connectors
	LED-CHL-W-MC				LTR-S-COB-24V-RGBTW and LOC6 Connectors
					LTR-S-COB-WP (Wet Location) and No Connectors

LED TAPE SLIM MUD-IN MOUNTING CHANNELS

PRODUCT DESCRIPTION

A slim format, extruded aluminum channel designed especially for mud-in installations. Available in 6' lengths, the aluminum perforated mud-in frame that flanks both sides of the channel enables easy mudding installation.



LED-CHL-MI-ISC6 extruded aluminum channel designed especially for inside corner mud-in installations



LED-CHL-MI-SST6 shown layed in with mud-in collar



LED-CHL-MI-SST6



LED-CHL-MI-OSC6 extruded aluminum channel designed especially for outside corner mud-in installations

		MOUNTING CHAN	CHANNEL COMPATIBLE TAPE		
	Catalog No.	Description	Length	Dimensions	Tape and Connectors
HT MUD-IN	LED-CHL-MI-SST6	Standard extruded aluminum mud-in slim channel. Includes snap-on frosted lens.	6'	-41"61" .73"51"2.09"	LTR-P Professional Series (Dry Location) and No Connectors LTR-E Economy Series and No Connectors LTR-S Specification Series (Single Color) and No Connectors
SLIM STRAIGHT MUD-IN	LED-CHL-MI-SST-EC	(2) End caps for LED-CHL-MI-SST6: one solid, one with hole	N/A		LTR-S-DTW (Dim to Warm) and No Connectors LTR-S-COB (Chip on Board) and No Connectors
IER MUD-IN	LED-CHL-MI-ISC6	Standard extruded aluminum mud-in inside corner channel. Includes snap-on frosted lens.	6'	1.02" 90° 1.81"	LTR-P Professional Series (Dry Location) and No Connectors LTR-E Economy Series and No Connectors LTR-S Specification Series (Single Color) and No Connectors
INSIDE CORNER MUD-IN	LED-CHL-MI-ISC-EC	(2) End caps for LED-CHL-MI-ISC: one solid, one with hole.	N/A		LTR-S-DTW (Dim to Warm) and No Connectors LTR-S-COB (Chip on Board) and No Connectors
INER MUD-IN	LED-CHL-MI-OSC6	Standard extruded aluminum mud-in outside corner channel. Includes snap-on frosted lens.	6'	1.99" 90° 90° 100° 100° 100° 100° 100° 100° 1	LTR-P Professional Series (Dry Location) and No Connectors LTR-E Economy Series and No Connectors LTR-S Specification Series (Single Color) and No Connectors
OUTSIDE CORNER MUD-IN	LED-CHL-MI-OSC-EC	(2) End caps for LED-CHL-MI-OSC: one solid, one with hole.	N/A		LTR-S-COB (Chip on Board) and No Connectors

LED TAPE STANDARD MUD-IN & CORNER CHANNELS

PRODUCT DESCRIPTION

Recess illuminated sections of light for clean looking and creative design options. The aluminum, perforated frame enables easy mud-in installation. Includes snap-on frosted lens to produce even illumination and reduce pixelization. Standard extruded inside and outside corner LED tape mud-in channels come complete with lens.



LED-CHL-MI-ST8-FC90 Flate corner shown



LED-CHL-MI-ST8-IC90 Inside corner shown





LED-CHL-MI-ST8-OC90 Inside corner shown


		MOUNTING CHAN	NEL		CHANNEL COMPATIBLE TAPE	
	Catalog No.	Description	Length	Dimensions	Tape and Connectors	
	LED-CHL-MI-ST6	Standard extruded aluminum mud-in channel. Includes snap-on frosted lens.	6'	1.81" -55" -39" -81" -1.12"	LTR-P Professional Series (Dry Location) and EST Connectors	
					LTR-E Economy Series and ST Connectors	
	LED-CHL-MI-ST8-FC90	90° Flat Corner for standard extruded aluminum mud-in slim channel. Includes snap-on frosted lens.	N/A		÷ 55 →	LTR-S Specification Series (Single Color) and EST Connectors
STANDARD FLAT MUD-IN	LED-CHL-MI-ST8-IC90	90° Inside Corner for standard extruded aluminum mud-in slim channel. Includes snap-on frosted lens.	N/A		LTR-S-COB (Chip on Board) and EST Connectors	
STANDAR					LTR-S-DTW (Dim to Warm) and EST Connectors	
	LED-CHL-MI-ST8-OC90	90° Outside Corner for standard extruded aluminum mud-in slim channel. Includes snap-on frosted lens.	N/A		LTR-S-RGBW (dry Location) and EZ Connectors	
	LED-CHL-MI-ST-EC	(2) End caps for LED-CHL-MI-ST6: one solid, one with hole.	N/A		LTR-S-TUN (Tunable White) and LTR-S-TUN Connectors	
	LED-CHL-MI-ST8-EC	(2) End caps for LED-CHL-MI-ST8: one solid, one with hole.	N/A		LTR-S-COB-24V-RGBTW and LOC6 Connectors	

LED TAPE COVE & WALK OVER MUD-IN MOUNTING CHANNELS

PRODUCT DESCRIPTION

An extruded dual aluminum channel designed especially for indoor or dry location mud-in cove installations. Available in 6' lengths, the curved striated aluminum mud-in frame that runs the length of the mounting channel enables easy mudding.






LED-CHL-MI-CMCH6 mounting channels comes inluded for Cove Channel



LED-CHL-MI-C6 extruded mud-in channel shown to scale



LED-CHL-WOD6 (top left) and LED-CHL-WOS6 (bottom right) deep mud-in walk over channels

		MOUNTIN	G CHANI	NEL	CHANNEL COMPATIBLE TAPE
	Catalog No.	Description	Length	Dimensions	Tape and Connectors
COVE WITH MOUNTING CHANNEL	LED-CHL-MI-C6	Standard extruded aluminum mud-in channel for coves. LED-CHL-MI-CMCH6 (included, see below) With frosted lens with mounting clips and screws.	6'	0° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.64° 1.6	LTR-P Professional Series (Dry Location) and EST Connectors LTR-E Economy Series and ST Connectors LTR-S Specification Series (Single Color) and EST Connectors LTR-S-COB (Chip in Board) and EST Connectors
WITH MOUN	LED-CHL-MI-CEC	(2) End caps for LED-CHL-MI-C6: one solid, one with hole.	N/A	2.54*	LTR-S-TUN (Tunable White) and No Connectors
COVE	LED-CHL-MI-CMCH6 (INCLUDED WITH LED-CHL-MI-C6)	Mounting channel (included) for LED-CHL-MI-C6 Cove channel.	N/A		LTR-S-DTW (Dim to Warm) and EST Connectors
SHALLOW	LED-CHL-WOS6	Standard extruded aluminum mud-in walk over shallow depth channel. Includes frosted lens (silicone required for installation).	6'	1.06" 1.2" † 1.375" -48" -84"	LTR-P Professional Series (Dry Location) and No Connectors LTR-E Economy Series and No Connectors
WALK OVER SHALLOW	LED-CHL-WOS-EC	(2) End caps for LED-CHL-WOS: one solid, one with hole.	N/A		LTR-S Specification Series (Single Color) and No Connectors LTR-S-DTW (Dim to Warm) and No Connectors LTR-S-TUN (Tunable White) and No Connectors
R DEEP	LED-CHL-WOD6	Standard extruded aluminum mud-in walk over deep depth channel. Includes frosted lens (silicone required for installation).	6'		LTR-P Professional Series (Dry Location) and EST Connectors LTR-E Economy Series and ST Connectors LTR-S Specification Series (Single Color) and EST Connectors
WALK OVER DEEP	LED-CHL-WOD-EC	(2) End caps for LED-CHL-WOD: one solid, one with hole.	N/A	.48"——	LTR-S-COB (Chip in Board) and EST Connectors LTR-S-TUN (Tunable White) and No Connectors LTR-S-DTW (Dim to Warm) and EST Connectors

LED TAPE OVERLAY LENS

A low-profile arched clear or frosted lens that surrounds any size LEDTask Series tape. Provides an economical protective shield while eliminating diode imaging. Easy to install and cuttable in the field. Made of lightweight polycarbonate plastic.







		MOUNTING CHANN	CHANNEL COMPATIBLE TAPE		
	Catalog No.	Description	Length	Dimensions	Tape and Connectors
		LED tape overlay lens. Clear polycarbonate plastic with 3M peel and stick adhesive rails. UV stable.			LTR-P Professional Series (Dry Location) and EST Connectors
	TOL4-CL		4'	1.45" \(\) 80" \(\)	LTR-E Economy Series and ST Connectors
LENS					LTR-S Specification Series (Single Color) and EST Connectors
OVERLAY LENS					LTR-S-COB (Chip on Board) and EST Connectors
TAPE 0V		LED tape overlay lens. Frosted polycarbonate plastic with 3M peel and stick adhesive rails. UV stable.	4'		LTR-S-DTW (Dim to Warm) and EST Connectors
LOGI	TOL4-FR			·	LTR-S-RGBW (dry Location) and EZ Connectors
					LTR-S-TUN (Tunable White) and LTR-S-TUN Connectors
					LTR-S-COB-24V-RGBTW and LOC6 Connectors

