

Path Light

ILS-P201-XX Large Hat Path Light Specification Sheet



PRODUCT OVERVIEW

The Irradiar Landscape Path Lights by GM Lighting are premium-grade, pathway lights designed to enhance outdoor spaces with subtle and even illumination. Engineered for functionality and style, these path lights feature durable construction and an elegant design, making them perfect for guiding pathways, accentuating garden beds, and adding ambiance to your landscape.

FEATURES

- Larger form for bigger scale applications
- Die-cast brass (6.8" Dia. x 24"H)
- Frosted glass / white reflector optics
- Antique Brass or Black finish
- Ground Stake (included)
- G4 LED lamps (not included)
- 360° downlight smooth distribution
- 6ft Direct Burial Cable, 18AWG

SPECIFICATIONS

ELECTRICAL

- 12V (nominal) low voltage
- 4W G4 (max lamp wattage)

CERTIFICATION

- cETLus
- IP65

WARRANTY

- 10 years (visit: gmlighting.net/warranty)

ORDERING INFORMATION:

1. SELECT FIXTURE

Product No.	Description
ILS-P201-AB	Antique Brass Large Hat Path Light

NOTE: For other finish options not shown, consult GM Lighting for availability

2. SELECT A COMPATIBLE GM LAMP

G4 (WP series, Water Protection): WHITE | G4 (Damp Location): WHITE

Watts	CCT	Lumens	WP series	Damp Location
2W	2700K	180lm	LG427K-02W0MWP	LG427K-02W01S
	3000K	180lm	LG430K-02W0MWP	LG430K-02W01S
	4000K	180lm	LG440K-02W0MWP	LG440K-02W01S
3W	2700K	270lm	LG427K-03W0MWP	LG427K-03W01S
	3000K	270lm	LG430K-03W0MWP	LG430K-03W01S
	4000K	270lm	LG440K-03W0MWP	LG440K-03W01S
4W	2700K	380lm	LG427K-04W0MWP	LG427K-04W01S
	3000K	380lm	LG430K-04W0MWP	LG430K-04W01S
	4000K	380lm	LG440K-04W0MWP	LG440K-04W01S

NOTE: Lamps must be used in an outdoor rated luminaire for landscape applications.

Project Name	Type
Catalog #	Date




Path Light

ILS-P201-XX Large Hat Path Light Specification Sheet



3. SELECT COMPATIBLE ACCESSORIES

Product No.	Description
ILS-A100P	ILS LG Stake W/Slot Black ABS 1/2 NPS
ILS-A110P	ILS SM Stake W/Slot Black ABS 1/2 NPS
ILS-A130-AB	ILS Stake Cover Brass Antique Brass Finish
ILS-A540-AB	ILS Round Surface Mount Brass, Antique Brass Finish Set Screw 3X SS Black Screws
ILS-A541-AB	ILS Cone Surface Mount Brass, Antique Brass Finish Set Screw 3x SS Black Screws
ILS-A530-AB	ILS Tri-Point Surface Mount Brass, Antique Brass Finish 3x SS Black Screws
ILS-A302-AB	ILS Direct Light Fitting Brass Internal 1/2" IPS Threads Antique Brass Finish
ILS-A700-AB	1/2" NPS Locknut Brass

 ILS LG Stake ILS-A100P	 ILS SM Stake ILS-A110P
 LS SM Stake Cover ILS-A130-AB	 ILS RND Surface Mount ILS-A540-AB
 ILS Cone Surface Mount ILS-A541-AB	 ILS Tri-Point Surface Mount ILS-A530-AB
 1/2" NPS Locknut Brass ILS-A700-AB	 ILS Fitting ILS-A302-AB

4. SELECT COMPATIBLE POWER SUPPLY

Fixtures must be used with 12V nominal power supply. See transformers specification sheets for details, controls and related accessories.

Product No.	Watts	Voltage
ILS-S075A-SS	75W	120Vin, 12/15Vout
ILS-S150B-SS	150W	120Vin, 12/13/14/15Vout
ILS-S300B-SS	300W	120Vin, 12/13/14/15/17/18/22Vout
ILS-S600B-SS	600W (2X300W)	120Vin, 12/13/14/15/17/18/22Vout
ILS-S100C-PC	100W	120Vin, 12/15Vout



Path Light

ILS-P201-XX Large Hat Path Light Specification Sheet



DIMENSIONS

